
AD A 053770



Report 2230

FORKLIFT TRUCKS, GASOLINE-ENGINE-DRIVEN, 4000- TO 6000-POUND-CAPACITY – USER SURVEY

> James E. Stephens, Jr. and Jesse W. Reid, Jr.

> > February 1978



Approved for public release; distribution unlimited.

U.S. ARMY MOBILITY EQUIPMENT
RESEARCH AND DEVELOPMENT COMMAND
FORT BELVOIR, VIRGINIA

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
223014 MERADCOM- 2230 GOVT ACCESSION NO	. 3. RECIPIENT'S CATALOG NUMBER
FORKLIFT TRUCKS, GASOLINE-ENGINE-DRIVEN,	5. TYPE OF REPORT & PERIOD COVERED
4000- TO 6000-POUND-CAPACITY – USER SURVEY	5. PERFORMING ORG. REPORT NUMBER
James E. Stephens, Jr. Jesse W. Reid, Jr.	B. CONTRACT OR GRANT NUMBER(*)
Mech & Constr Eqpt Lab, ATTN: DRDME-HM U.S. Army Mobility Equipment Research and Development Command, Fort Belvoir, Virginia 22060	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
1. CONTROLLING OFFICE NAME AND ADDRESS Commander U.S. Army Mobility Equipment Research and Development Command, Fort Belvoir, Virginia 22060	February 1978
4. MONITORING AGENCY NAME & ADDRESS(If different from Controlling Office)	UNCLASSIFIED
	154. DECLASSIFICATION/DOWNGRADING SCHEDULE
Approved for public release; distribution unlimited.	D D C
7. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different fr	om Report)
8. SUPPLEMENTARY NOTES	
9. KEY WORDS (Continue on reverse side if necessary and identify by block number Maintenance Forklift Truck Reliability, Availability, and Gasoline Engine Quality Assurance Specification Procurement	
This report is the result of recent emphasis on procuring Adaptation of Commercial Items (MACI). Four major surveyed, and their candidate models for the three size requi users of these forklift trucks were then visited by a Survey naire designed to obtain the data required. This report pre conclusions of evaluating the established commercial market forklift trucks.	forklift truck manufacturers were rements were obtained. Commercial Team using a User Survey Questionsents the methodology, results, and

403 16 \$

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Date Entered)

(Block 20 Cont'd)

The compiled results are discussed and commercial forklift trucks are compared for variance with the requirements of the existing MACI specification for forklift trucks.

The Survey results support the general conclusions: The Reliability, Availability, and Maintainability (RAM) characteristics of the commercial forklift trucks surveyed are acceptable to their commercial users.

CONTENTS

Section	Title	Page
	ILLUSTRATIONS	iv
	TABLES	v
	METRIC CONVERSION FACTORS	vi
I	INTRODUCTION	
	 Background Description of Material Objective Scope 	1 1 2 2
II	USER SURVEY	
	5. Preparation of the User Survey Questionnaire6. Selection of Users to be Surveyed	13 13
III	RESULTS OF USER SURVEY	
	7. Life-Cycle Management	13
IV	CONCLUSIONS	
	8. Conclusions	20
	APPENDICES	
	A. Questionnaire for User Evaluation of Commercial Forklift Trucks	21
	B. Compiled Results from Survey of Industrial Forklift Users	34

ILLUSTRATIONS

Figure	Title	Page
1	Allis-Chalmers Forklift Truck Similar to Model ACC45B	3
2	Allis-Chalmers Forklift Truck Similar to Model ACP70	4
3	Clark Forklift Truck, Model C300-40	5
4	Clark Forklift Truck, Model C500-Y70	6
5	Hyster Forklift Truck Similar to Model S50C	7
6	Hyster Forklift Truck, Model H70C	8
7	Towmotor Forklift Truck Similar to Model T40B	9
8	Towmotor Forklift Truck, Model T50B	10
9	Towmotor Forklift Truck, Model V60B	11
10	Forklift Truck Procured by Using Military Specification MIL-T-52862	12

TABLES

Number	Title	Page
1	Forklift Trucks Listed by the Four Manufacturers Surveyed	1
2	Industrial Users Surveyed and Manufacturers and Models Surveyed	14
3	Various User Responses to User Survey Questionnaire Concerning Warranties of 4000-Pound SRT and 6000-Pound PT Commercial Forklift Trucks	15
4	RAM Data from a Lease-Fleet Operator	16
5	5000- and 6000-Pound-Capacity Forklift Trucks Maintainability Indices Calculated from Lease-Fleet Data	16
6	Commercial Maintainability Indices Versus Requirements of MIL-T-52862	16
7	User Responses to RAM-Related Questions	17
8	Average Time to Remove and Replace Frequently Replaced Components	18
9	Removal/Replacement Times from User Surveys Versus Requirements from the Existing Specification (MIL-T-52862)	18
10	Distribution of Fuel Types Used by Industrial Users Surveyed	19
1,1	Significant Differences Expected Between Forklift Trucks Procured Using a Commercial Rather than a MACI Specification	20

INANNOUNCE	Buff Section I
BY PATRIBUTIO	IN/AVAILABUITY CO.T.S
Dist. At	AIL. ann

METRIC CONVERSION FACTORS

Approximate Conversions to Metric Measures

Symbol	When You Know	Multiply by	To Find	Symbo
		LENGTH		
	notice the state of the state of			
in	inches	*2.5	centimeters	cm
ft	feet	30	centimeters	cm
yd	vards	0.9	meters	m
mi	miles	1.6	kilometers	km
	et findes, her <u>e so</u>	AREA		
in ²	square inches	6.5	square centimeters	cm ²
in ² ft ² yd ² mi ²	square feet	0.09	square meters	m ²
vd ²	square yards	0.8	square meters	m ²
mi ²	square miles	2.6	square kilometers	km ²
	acres	0.4	hectares	ha
		IASS (weight)		
oz	ounces	28	grams	9
lb	pounds	0.45	kilograms	kg
	short tons	0.9	metric tons	t
	(2000 lb)	VOLUME		
		VOLUME		
tsp	teaspoons	5	milliliters	ml
Tbsp	tablespoons	15	milliliters	ml
fl oz	fluid ounces	30	milliliters	ml
C	cups	0.24	liters	L
pt	pints	0.47	liters	L
qt	quarts	0.95	liters	L
gal	gallons	3.8	liters	L
ft ³	cubic feet	0.03	cubic meters	m ³
yd ³	cubic yards	0.76	cubic meters	m^3
	TEMP	ERATURE (exact)		
°F	Fahrenheit	5/9 (after	Celsius	"c
	temperature	subtracting 32)	temperature	

^{• 1} in = 2.54 cm (exactly).

		Annouimete Conu		-i- ••	
		Approximate Conv	ersions from Met	ric Measures	
22					
_ ~	Symbol	When You Know	Multiply by	To Find	Symbo
2					
			LENGTH		
8					
		millimeters	0.04	inches	in
2	mm		0.04	inches	
_ =	cm	centimeters	0.4	inches	in
	m	meters	3.3	feet	ft
=	m	meters	1.1	yards	y
	km	kilometers	0.6	miles	m
		Kilonio Colo	0.0		
_ 11					
			AREA		
_					
	cm ²	square centimeters	0.16	square inches	in
15	m ²				
	m ,	square meters	1.2	square yards	yd mi
	km ²	square kilometers	0.4	square miles	mi
_ =	ha	hectares (10 000 m	2.5	acres	
13					
_			MASS (weight)		
12					
	9	grams	0.035	ounces	0
	kg	kilograms	2.2	pounds	It
_ =	1	metric tons (1000 kg		short tons	
				Smart tono	
_ 9					
_ =					
			VOLUME		
•					
_					
	ml	milliliters	0.03	fluid ounces	fl o
•	L	liters	2.1	pints	pt
	L	liters	1.06	quarts	qt
	Ī,	liters	0.26	gallons	gal
-	m³				ft ³
	m a	cubic meters	35	cubic feet	π
	m ³	cubic meters	1.3	cubic yards	yd ³
_ •					
-		TEM	PERATURE (exac	••1	
		16.00	LEUNIONE (AVE	<u>-()</u>	
•	°c	Celsius	9/5 (then	Fahrenheit	
_	•				
		temperature	add 32)	temperature	
_				. 0	
		°F 32	00.0		2
64			98.6		-
	-	-40 0 40	80 120	160 200	
			╒╸┖╺╏╸┖╺╏╸		
		-40 -20 0	20 40 37	60 80 10	00

FORKLIFT TRUCKS, GASOLINE-ENGINE-DRIVEN,

4000- to 6000-POUND CAPACITY - USER SURVEY

I. INTRODUCTION

- 1. Background. On 24 May 1976, the Office of Management and Budget directed the Government to emphasize the acquisition of commercial, off-the-shelf products in order to achieve optimal effectiveness in supply support operations. The resulting emphasis on procurement of commercial products included forklift trucks used by the Army. Therefore, a program was undertaken by MERADCOM to develop a procurement document whereby commercial, off-the-shelf, forklift trucks can be procured and supported. The major elements in this program are as follows:
 - a. Prepare the Manufacturer Survey Questionnaire.
 - b. Conduct and report the Manufacturer Survey.
 - c. Prepare the User's Survey Questionnaire.
 - d. Conduct and report the User Survey.
 - e. Develop the procurement specification.
 - f. Procure commercial forklift trucks.
 - g. Type classify.

The first two program elements have been completed and are reported separately.*

2. Description of Material. Table 1 summarizes the forklift truck described by each manufacturer in the Technical Information Packages submitted to MERADCOM.

Table 1. Forklift Trucks Listed by the Four Manufacturers Surveyed

	Model No.				
	4000-lb Solid-	4000-lb Solid-	6000-lb		
Manufacturer	Rubber Tire (SRT)	Rubber Tire (SRT)	Pneumatic Tire (PT)		
	(144-in. lift height)	(180-in. lift height)	(180-in. lift height)		
	Size 1	Size 2	Size 3		
Allis-Chalmers	ACC45B	ACC45B	ACP70		
Clark	C300-40	C300-40	C500-Y70		
Hyster	S50C	S50C	H70C		
Towmotor	T40B	T50B	V60B		

J. E. Stephens, Jr. and J. W. Reid, Jr.; "Forklift Gasoline-Engine-Driven, 4000- to 6000-Pound-Capacity - Manufacturers Survey." MERADCOM Report 2231; November 1977.

These forklift trucks are shown in Figures 1 through 9. The four manufacturers described their forklift trucks as "commercial, off-the-shelf, forklift trucks" which would satisfy the Army's requirement for three different sizes of forklift trucks. The following general requirements for these three sizes were provided each manufacturer and correlate to the listings in Table 1.

	Size 1	Size 2	Size 3
Lift Capacity (lb):	4000	4000	6000
Lift Height (in.):	144	180	180
Load Center (in.):	24	24	24
Engine (type):	Gasoline	Gasoline	Gasoline
Tire (type):	Solid-Rubber	Solid-Rubber	Pneumatic
Transmission:	Automatic	Automatic	Automatic
Manueverability (right-angle-tur	n dimension (in.)	48-in. by 48-in.	pallet):
Without Sideshifter (in.):	150	156	196
With Sideshifter (in.)	154	160	200
Ambient Temperature Range:	0° - 110°F	0° - 110°F	$0^{\circ} - 110^{\circ} F$
Typical Use:	In general warel installations.	nouses, depots, a	nd other defense

Finally, an important conclusion contained in the manufacture survey report is: Forklift trucks used by Industry do not differ significantly from forklift trucks previously procured by the Army using Military Specification MIL-T-52862. A fork-lift truck procured using this specification is shown in Figure 10. This specification was also assumed to represent the requirement for commercial forklift trucks in lieu of a formal requirement such as a Required Operational Capability (ROC).

3. Objective. The objective of this survey is:

- a. To assess the Reliability, Availability, and Maintainability (RAM) characteristics of the four forklift trucks using data solicited from industrial users.
- b. To determine the procedure used by Industry to procure commercial forklift trucks.
- c. To determine Industry's management philosophy for the forklift truck's life cycle.
- 4. Scope. This report considers the third and fourth elements of the MERADCOM program designed to support procurement of commercial, off-the-shelf, forklift trucks. These elements are:




Figure 1. Allis-Chalmers forklift truck similar to Model ACC45B.




Figure 2. Allis-Chalmers forklift truck similar to Model ACP 70.




Figure 3. Clark forklift truck, Model C300-40.




Figure 4. Clark forklift truck, Model C500-Y70.




Figure 5. Hyster forklift truck similar to Model S50C.



Figure 6. Hyster forklift truck, Model H70C.




Figure 7. Towmotor forklift truck similar to Model T40B.



Figure 8. Towmotor forklift truck, Model T50B.




Figure 9. Towmotor forklift truck, Model V60B.



Figure 10. Forklift truck procured by using Military Specification MIL-T-52862.

- a. Prepare the User Survey Questionnaire.
- b. Conduct and report the User Survey.

II. USER SURVEY

- 5. Preparation of the User Survey Questionnaire. As discussed previously, the existing specification for this item, MIL-T-52862, was assumed to represent the requirement for forklift trucks. MERADCOM prepared a comprehensive questionnaire (Appendix A) to solicit from commercial users the data necessary to determine the extent to which commercial forklift trucks complied with this specification. Additional questions were added to determine Industry's life-cycle management philosophy for forklift trucks, to assess RAM, and to determine the manufacturer, dimensions, and part number of each major component.
- 6. Selection of Users to be Surveyed. The names of industrial users and their servicing dealers were obtained from four manufacturers surveyed previously. The program goal was to survey at least three major users of each forklift model proposed by the manufacturer. Twenty users (Table 2) were visited by the survey team. Survey team members included representatives from MERADCOM (engineering) and TARCOM (Quality Assurance/Maintenance). The survey team recorded the findings of their visits on the User Survey Questionnaires (Appendix A).

III. RESULTS OF USER SURVEY

- 7. Life-Cycle Management. All users were cooperative and attempted to provide the data solicited by the survey team. The compiled results from the User Survey Questionnaires are presented in Appendix B. A discussion of industrial users' life-cycle management policies for 4000-lb solid-rubber-tire (SRT) and 6000-lb pneumatic-tire (PT) forklift trucks follows:
- a. Industry purchases each forklift truck for a specific task and equips it to match the work station environment. This is practical and cost-effective, as Industry generally can assume the forklift truck will be assigned to one work station all of it's economic life.
- b. Industrial users are not committed to the concept of purchasing a fork-lift truck merely because it has the lowest initial cost. Instead, preference for a make/model, past performance, dealer location, dealer reputation, parts availability, and lowest cost to own were cited as reasons for purchasing a specific make/model. Obviously, quantifying these factors is difficult, especially when separate plants within the same corporation prefer different make/model forklift trucks. From user comments, this preference for a specific make/model can be related to two factors: the

dealer and the operator. A strong local dealer, able to support the user's vehicle logistically, regardless of make surveyed, definitely has an advantage when the user re-buys. Finally, based on preconceived feelings about a certain make/model of fork-lift truck, the operator/mechanic may question the acceptability of an alternate make/model. Therefore, if prices are within reason, users tend to buy for reasons other than initial cost.

Table 2. Industrial Users Surveyed and Manufacturers and Models Surveyed

			Manufacturer			
Type Fuel		User	Hyster	Clark	Towmotor	Allis-Chalmers
Diesel	A1	Port of Tacoma				ACP-70
LPG	A1	Port of Tacoma				ACC-55
LPG	C1	Borden, Inc.		C500-70		
LPG	C2	Citrus World		C500-50		
LPG	C3	Tropicana Prod.		C500-40		
				C500-55		
LPG	C4	Central Hardware		Ç300-40		
LPG	C5	Scotty's Ind.		C300-40		
LPG	H1	Champion Intl. Corp.	S50C			
LPG	H2	Hunt-Wesson Foods	S50C			
LPG	НЗ	Weyerhauser	S50C			
LPG	H4	Weyerhauser	H70C			
Gas	H5	Kaiser Alum. & Chem.	H60C			
Gas	H6	Kaiser Alum	H80C			
LPG	T1	Frontier Airlines			V55B	
Gas	T1	Kaiser Alum			V60B	
LPG	T2	High Resources, Inc.			T40B	
LPG	T3	Highland Resources, Inc.			T50B	
LPG	T4	Owens-Corning			T40B	
LPG	T5	Owens-Corning			T50B	
Diesel	T6	US Pipe & Foundry			V60B	

LPG - Liquefied Petroleum Gas

c. Table 3 reveals that only 50 percent of the users surveyed correctly stated the warranty provision for their forklift trucks. Two users specified a warranty period in excess of the manufacturer's standard warranty. This low awareness factor is indicative of Industry's general opinion that warranties are not important. This opinion can probably be traced to the rapport that has developed between the user/dealer. Users cited instances of dealers correcting failures which occurred beyond the warranty period. Such dealers typically are well considered when it's time to re-buy. However, several users experienced difficulty invoking the warranty because of agreements with their mechanics' unions. These agreements prohibit anyone other than union personnel from working on the user's equipment. In these instances, the dealer

and user would make some equitable arrangement to reimburse the user for the labor costs incurred to correct the failure.

Table 3. Various User Responses to User Survey Questionnaire Concerning Warranties of 4000-Pound SRT and 6000-Pound PT Commercial Forklift Trucks

User Response	Number of Users with This Response
Same as manufacturers' standard warranty.	8
Conflicts with manufacturers' standard warranty.	5
User did not know provisions of warranty.	4
User is lessor and did not know warranty provisions.	aldesgraves to and the other
User specifies warranty.	2

- d. The industrial users' acceptance procedures are lax by Government standards but are also indicative of their confidence in their local dealers. The dealer services the forklift truck and then delivers it to the user. The user, at most, may inspect the forklift truck to verify receipt of the make/model and optional equipment ordered. It is significant to note that even ir large corporations which purchase through their national accounts offices, the forklift trucks are purchased from and delivered and serviced by local dealers.
- e. Industrial users, in general, do not keep the (maintenance) records required to support an objective RAM assessment. Typically, the user charges a fork-lift truck with all of its maintenance time/parts/supplies, but when asked, most users could not discriminate between scheduled and unscheduled maintenance. Late in the program, lease-fleet operators were considered as a source of data to assess the RAM characteristics of these forklift trucks. A visit to one dealer with a large lease operation yielded the data shown in Table 4. These data were used to calculate the maintainability indices shown in Table 5 for commercial forklift trucks. As shown in Table 6, these values correlate favorably with the requirements from MIL-T-52862, the existing MACI specification. The values in Table 6 were derived using the same failure criteria. However, the test procedures are rigorous in the specification compared to the unknown of commercial use. This comparison validates the concept of commercial forklifts and supports the subjective evaluation of RAM using User Survey data.

Although an objective assessment of RAM could not be made using data from the user survey, a subjective evaluation is possible. Table 7 was prepared to highlight the user's response to several questions related to the RAM characteristics of the forklift trucks surveyed. The response indicates the general acceptability of

commercially available 4000-SRT/6000-PT forklift trucks, as 100 percent of the users stated they would re-buy the identical make/model.

Table 4. RAM Data from a Lease-Fleet Operator

Item	5000-lb	7000-lb
Blackers Commence Standard Security	Forklift	Forklift
Total active maintenance time (man-hours)	200.00	220.0
Total operational time (hours)	10,000	10,000
Total number of scheduled and unscheduled maintenance actions	80	80
Total number of chargeable failures (requires 1 hour or more to repair)	20	20
Total man-hours to repair chargeable failures	110.0	130.0
Total scheduled and unscheduled maintenance time (clock-hours)	200.0	222.0
Number of vehicles in fleet	60	60

Table 5. 5000- and 6000-Pound-Capacity Forklift Trucks Maintainability Indices Calculated from Lease-Fleet Data

Item	5000-lb-Capacity Forklift	7000-lb-Capacity Forklift 0.022	
Maintenance ratio (MR)	0.02		
Mean time between failures (MTBF)	500	500	
Mean time to repair failures	5.5	6.5	
Availability (achieved)	0.98	0.98	

Table 6. Commercial Maintainability Indices Versus Requirements of MIL-T-52862

Item	MIL-T-52862	Commercial 5000-lb-Capacity Forklift	Commercial 7000-lb-Capacity Forklift
Mean time between failures (hours)	100	500	500
Maintenance Ratio (MR)	0.06	0.02	0.022

Table 7. User Responses to RAM-Related Questions

	Question	Unknown	Yes	No
1.	Would you rebuy an identical make and model forklift truck?	Ned Stote	20	
2.	Are you dissatisfied with any features of this equipment?		7 (1) (3) (5) (7)	13
3.	Are there any undesirable or unsatisfactory operating characteristics associated with this equipment?		2 (4) (8)	18
4.	Does the forklift perform satisfactorily under the conditions where used?		20 (2)	
5.	Are delays caused by part unavailability?	4		16
6.	Can operators and/or maintenance personnel be trained without difficulty?		20	
7.	Are there unduly difficult or time-consuming maintenance tasks which contribute to unavailability?	2	2 (6)	16
8.	Are all components accessible for maintenance?	2	17	1
9.	Have any difficulties been encountered using the maintenance literature?	2		18

(1) Poor visibility through mast.

(2) Overheats if radiator isn't cleaned frequently with compressed air.

(3) Brake/inching and accelerator are too close.

(4) Truck overheats.

(5) Replacing unsatisfactory slide masts with roller masts.

(6) R/R of water pump is difficult.

(7) Seal failure in hydraulic pumps permits an interchange of engine oil/hydraulic fluid.

(8) Retaining bolt to lift cylinder strips.

f. The maintenance times associated with frequently performed removal/replacement tasks were estimated by the users surveyed and are shown in Table 8. These items were averaged, and in Table 9 they have been compared to the maintenance times allocated in the existing specification (MIL-T-52862). As can be seen, these average times correlate well with the requirements from the existing specification.

Table 8. Average Time to Remove and Replace Frequently Replaced Components

			Remova	al/Replacemen	Time (Min	utes) by	Compone	ent
User	Forklift	Hyd Pump	Starter	Voltage Regulator	Battery	Fan Belt	Brake Shoes	Alternator
C1	Clark							
	C500 Y 70	180	120	60	60	60	640	120
C2	Northwestern							
	C500 50	90	60	15	15	20	300	45
C3	C500 40/55	60	60	20	10	15	360	30
C4	C300 40	U	U	U	U	U	U	U
C5	C300 50	U	U	U	U	U	U	U
A1	ACC 55	U	U	U	U	U	U	U
A2	ACP70	U	U	U	U	U	U	U
T1	V55B	U	60	25	20	60	U	30
T2	T40B	135	35	17.5	10	60	120	35
T3	T50B	135	35	17.5	10	60	120	35
T4	T40B	120	60	15.0	15	30	360	15
T5	T50B	120	60	15	15	30	360	15
T6	V60B	90	45	30	5	30	60	30
H1	S50C	45	30	30	10	5	120	15
H2	S50C	45	120	10	10	30	240	120*
НЗ	S50C	120	45	10	10	10	240	45
H4	H70C	120	45	10	10	10	240	45
H5	H60C	120	20	10	10	20	120	U
H6	H80C	75	20	10	20	20	120	15

U - Unknown

Table 9. Removal/Replacement Times from User Surveys Versus Requirements from the Existing Specification (MIL-T-52862)

Component Removed/Replaced	Removal/Replacement Time (Minutes) User Survey MIL-T-52862		
Starter	50	60	
Voltage Regulator	18	30	
Battery	14	30	
Fan Belt	29	75	
Alternator	19*	30	

^{*} Estimate of Users C1 and H2 omitted.

^{*} User standardizes on alternators and mounts standard alternator when OE fails. This retrofit time of 120 min. occurs once per vehicle with a non-standard alternator.

g. Table 10 was prepared from survey results to highlight the distribution of various fuel types. Seventy-five percent of the users have equipped their forklifts to use LPG. Two users have diesel-powered, 6000-lb PT forklift trucks. It is significant to note that 85 percent of the users have selected a fuel type other than gasoline. This statistic becomes more impressive when one considers the program objective was to survey gasoline-powered forklifts which were difficult to find. The findings of this survey may signal that the Army should revalidate its requirement for gasoline-powered materials-handling equipment in lieu of LPG for the 4000-lb applications and/or diesel for 6000-lb and larger applications.

Table 10. Distribution of Fuel Types Used by Industrial Users Surveyed

Fuel Type	Number of Users
Gasoline	3
Diesel	2*
LPG	15

^{*} Used in 6000-pound forklift trucks.

- h. Most users either implicitly expect or explicitly state their equipment, when delivered, is to comply with all applicable State and Federal Safety Codes (including OSHA) and ANSI Safety Standards for powered industrial trucks. Only one user specified "... a maximum sound level not to exceed 96 dB(A) at full power, in an open area without reverberation and 70 dB(A) ambient" All users surveyed stated the sound level did not result in unusual operator fatigue after prolonged operations.
- i. Finally, it should be noted that industrial users are not reluctant to specify equipment to match their requirement, even if it precludes competitive bidding. As examples, one user specified 2-stage air cleaners followed by an oil bath; another user specified vehicle to be compatible with glycol-based hydraulic fluid.
- j. As discussed previously, industrial users are not committed to the philosophy of purchasing a forklift merely because it has the lowest initial cost. This stance was supported by reasons such as dealer proximity, good dealer service, good parts availability, and preference for a make/model. All of these reasons relate to the user's ability to logistically support his truck. It is interesting to note that two users, remote from any dealer, use manual transmissions which their mechanics can service/rebuild rather than automatic transmissions normally rebuilt by the dealer. Regardless of make/model, most users stated that part availability was 48 hours or less. However, all users avoided, whenever possible, the use of high-cost Original Equipment Manufacturer (OEM) parts by purchasing them from their local parts jobber. Preference for a make/model permits the industrial user to justify stocking a larger range of

spare parts (extra motor, transmission, etc.). This preference for a make/model also eliminates training problems; consequently, the industrial users were content with the manufacturers' publications.

k. In summary, the results of the manufacturers' survey and this survey have been analyzed and combined to derive a listing of the significant differences to be expected between MACI-type forklifts (MIL-T-52862) and commercial forklifts (MIL-T-52932). These differences are shown in Table 11.

Table 11. Significant Differences Expected Between Forklift Trucks Procured
Using a Commercial Rather Than a MACI Specification

Feature	Commercial (MIL-T-52932)	MACI (MIL-T-52862)
Electromagnetic Interference requirement	No	Yes
Noise Level Specified	No	Yes
Diesel Engine Option (6000-lb)	No	Yes
Rain/Starting Test Demonstration	No	Yes
Hydraulic System Contamination Level Specified	No	Yes
Fungus and Moisture Resistance Specified	No	Yes
Rearward Tilt	6°	8°
Fork Length	42 in.	40 in.

IV. CONCLUSIONS

8. Conclusions. It is concluded that:

- a. The RAM characteristics of the forklift trucks surveyed are acceptable to their industrial users.
- b. Industrial users cite reasons other than lowest initial cost for purchasing a particular make/model forklift.
- c. Industrial users purchase forklift trucks for a specific task in a known work station environment, and once purchased, a truck is assigned to that work station all of its economic life.
- d. Industrial users are not hesitant to prepare a specification to match their requirement even if it precludes competitive pricing.

APPENDIX A

QUESTIONNAIRE FOR

USER EVALUATION OF COMMERCIAL FORKLIFT TRUCKS,

PNEUMATIC- OR SOLID-RUBBER-TIRED, GASOLINE-ENGINE-DRIVEN,

COMMERCIAL MATERIALS-HANDLING EQUIPMENT

(CMHE)

USER:		
NAME		
ADDRESS	s	
TELEPHO	ONE	
CONTAC	Т	
EVALUATORS:		
NAME		ORGANIZATION
ENERGINETAL	TOTAL PERSON	RANGE OF SERVICE STREET
	60(043)	-
	 -	

A.	End	l Item:	prized appearing spine used spendes dend activisment (9)	
	1.	Manu	ufacturer	
	2.	Mode	el No	
	3.	Date	purchased	
	4.	Capa	city	
	5.	Load	center	
	6.	Tires	: SRTPNEU	
B.	Hov	w was i	item purchased?	
	1.	By sp	pecification: Sole SourceCompetitive Bid	
	2.	By de	ealer or mfgr recommendation	
	3.	From	n commercial brochure	
	4.	Othe	т	
	5.	Was	vehicle purchased newusedused	
C.	Con		nts and Accessories:	
	1.	Engir		
			ModelYear	
		(a)	Governor type (velocity, centrifugal):	
			Air cleaner mfgr, type, and part number:	
		(c)	Positive crankcase ventilation system?Yes	No
		(d)	Cooling system: Capacityqt Pressure	lb/in²
		(e)	Oil filter mfgr and part number:	
		(f)	Battery model, voltage, and capacity:	
		(g)	Alternator mfgr and part number:	
		(h)	Starter mfgr and part number:	
	2.	Powe	r Train:	
		(a)	Transmission mfgr and part number:	
			Front axle mfgr and part number:	
	3.		ing and Brakes:	
			Is nower steering furnished? Yes No.	

	(b)	Is steering pump separate from main hydraulic pump?YesNo
	(c)	Power steering pump mfgr and part number:
	(d)	Power steering control unit mfgr and part number:
	(e)	Is power brake furnished?YesNo
	(f)	Brake valve mfgr and part number:
4.	Hyd	raulic System:
	(a)	Filter mfgr and part number:
	(b)	Main pump mfgr and part number:
5.	Upri	ghts, forks, fork carrier, and load backrest:
	(a)	Mast roller or slider type?
	(b)	Number of mast stages:
	(c)	Mast part number:
	(d)	Load backrest type and part number:
	(e)	Sideshifter?No
	(f)	Sideshifter mfgr and part number:
6.	Wha	t instruments, gauges, and safety devices are furnished?
	(a)	Hourmeter:
	(b)	Ammeter: GaugeLight
	(c)	Engine coolant temperature: GaugeLight
	(d)	Engine oil pressure: GaugeLight
	(e)	Fuel gauge:
	(f)	Transmission pressure: GaugeLight
	(g)	Transmission temperature: GaugeLight
	(h)	Keyed ignition switch:
	(i)	Rear view mirror:
	(j)	Overhead guard:
	(k)	Load backrest:
	(1)	Horn:
	(m)	Floodlight(s)?YesNoQuantity
	(n)	Taillight?YesNo

		(o) Directional lights?No					
		(p) Parking brake?No					
		(q) Tilt cylinder anti-cavitation? Yes No					
		(r) Neutral start switch? Yes No					
		(s) Starter disconnect?YesNo					
	7.	What optional equipment is utilized?					
		(a) Sideshift:					
		(b) Retractable overhead guard:					
		(c) Attachments (clamps, ram):					
		(d) Special lights:					
D.	Fur	actional Performance and Characteristics:					
	1.	Geographical location (city and state):					
	2.	Approximate time truck operates outdoors:					
	3.	Is truck stored outdoors in cold climate?					
	4.	Has there been any difficulty starting truck in cold weather?					
	5.						
less	6.	Have there been any unusual environmental conditions (i.e., rain, contami-					
nat	ed are	eas, dirt)?					
	7.	Did the forklift perform properly under these conditions?					
y (st.	8.	What, if any, actions were required to enable proper operations?					
E.	Life	e-Cycle Information:					
	1.	Date put in service:					
	2.	2. Expected annual usage (hours):					
	3.	Expected time between major overhauls (hours):					
	4.	Expected life of the forklift (hours):					
F.	Cha	racteristics:					
	1	Does the engine operate on unleaded fuel?					

2.	Is fu	uel filter provided?						
3.	What is the capacity of the fuel tank?							
4.	Wha	What is capacity of the cooling system?						
5.	Non	Normal operating temperature range:						
6.	Air	Air Cleaner System: Oil BathDry						
7.	Rest	Restriction Indicator?YesNo						
8.	Loca	ation of air intake:						
9.	Doe	s the drive-train contain the following components:						
	(a)	Torque converter?YesNo						
	(b)	Power shift transmission? Yes No						
	(c)	Hydrostatic transmission?YesNo						
	(d)	Differential?No						
	(e)	Positive inching? Yes No						
	(f)	External transmission filter?YesNo						
	(g)	Water cooler for transmission?YesNo						
	(h)	Universal joint drive shaft? Yes No						
10		tircal System:						
		Protected by:Fuses?						
		Alternator furnished?Generator furnished?						
Con		bility with Related Equipment:						
1.		asportation:						
		Have you experienced difficulties in movement of this forklift to any						
site?								
311,		What kind of equipment have you used to transport the forklift?						
ahi	(c)							
shipn		What, if any, difficulties have been encountered?						

G.

job

of

2.	Service Equipment:		
	(a) Are any special tools required for servicing this forklift? If so, what		
tools?_			
forklift	(b) Is any special equipment other than special tools required for this		
	(c) Have any difficulties been experienced in using various tools required s forklift?		
	(d) What tools have you used?		
H. Pi	nysical Characteristics:		
1.	Length w/forks:w/o Forks:		
2.	Width:		
3.	Overhead guard height:		
4.	Collapsed mast height:		
5.	Maximum fork height:		
6.	Free lift:		
7.	Backrest height:		
8.	Tilt forward:Rearward:		
9.	Sideshift left:Right:		
10.	Carriage width:		
11.	Fork dimension: Length: Width: Thickness:		
12.	Do forks comply with ANSI MH11.4 (Hook-type mount)?YesNo		
13.			
	ım:Maximum		
14.			
15.			
	Drive tire trend width (C to C):		

17. Steer-tire tread width (C to C):				
18.	Driv	Prive tire: Size:Number:		
19.	Stee	er tire: Size:		
I. Reli	abilit	y, Availability, and Maintainability Characteristics:		
1.	General Data:			
	(a)	Normal workday in clock-hours:		
	(b)	Number of shifts per day:		
leggiger a	(c)	Total number of malfunctions requiring corrective maintenance:		
	(d)	Total clock-hours expended to perform corrective maintenance:		
	(e)	Total man-hours expended to perform corrective maintenance:		
	(f)	Organizational:		
	(g)	Dealer:		
	(h)	Average downtime awaiting parts not in stock at dealer location:		
tribute m	(i)	What, if any, particular systems or component failures (trend) conto non-availability?		
tenance,	(j) or pa	Do special tools, repair parts, technical assistance, inadequacies in main- rts publications contribute more to non-availability?		
a modifi		Is non-availability contributed to by design deficiency or the need for		
	(1)	What type of maintenance is performed by the: (1) Operator?		

(2) Mechanics?
(m) Are any components replaced on a scheduled basis? If so, what components and what intervals?
(n) Are you dissatisfied with any features of the equipment or your relationship with the manufacturer or dealership? If so, specify:
(o) Are there any undesirable or unsatisfactory operating characteristics associated with the equipment? If so, specify:
(p) Since purchasing the forklift, have there been any modifications of a corrective or improvement nature made by: (1) Manufacturer:
(2) Dealer:
(3) In-House:
(q) Have there been any significant design changes to this model item in the last year of which you are aware?

	(r)	Do all compar	rtments permit ready access to	all items requiring periodic
mainten	ance?			
	(s)	Is replacemen	t and adjustment of compone	ents and accessories accom-
plished	with r	minimum draina	age and/or distrubance to othe	r components?
purpose	(t) tools		naintenance accomplished w	
as cold			problems resulting from extre	
suming (maintenance tasks that are unneareastate maintenance.	
one man	using	g common tools	Please indicate the interval are and any special tools furnished	
1.	Rep	lace Filters:		
	(a)	Engine oil:	Interval	Time
	(b)	Air:	Interval	Time
	(c)	Fuel:	Interval	Time
	(d)	Transmission:	Interval	Time
	(e)	Hydraulic:	Interval	Time
2.	Dra	in and refill:		
	(a)	Engine Oil:	Interval	Time
	(b)	Transmission	Interval	Time

		(c)	Hydraulic Oil:	Interval	Time
		(d)	Cooling System:	Interval	Time
	3.	Lub	rication:	Interval	Time
		(a)	Preventative	Maintenance Time:	
			(1) Man-ho	urs expended for dai	ly servicing (average):
			(2) Man-ho	urs expended for we	ekly preventative maintenance service
(ave	erage)	:	9 2470 4210	at someon to the	and the state of t
			(3) Man-ho	urs expended for	monthly preventative maintenance
serv	rice (avera	ge):		et bise for gripper linearings of
of t	man	using	g common too	ols and special tools fu	e indicate the average time required for urnished with the unit to perform each verage time to remove and replace is as
	1.	Alte	rnator:		South Control of the
	2.	Star	ter:	<u> </u>	
	3.	Vol	tage regulato	r:	AL FOLKMAND OF MICHOLOGIC STATES OF STATES
	4.				
	5.				
	6.	Hyd	raulic pump:		
	7.				
L.	Safe	ety an	d Human Fac	tors (User Comments	
	1.				y the manufacturer augmented by the
usei	?			**	
	2.	Do	ou know of a	iny safety hazards tha	at exist during:
		(a)			
		(b)		150	
	3.				factors items/elements, furnished as
stan				ent, adequate:	Table 10000, ordinates, Talifornia us
		(a)	Gauges and r	nonitors:	

		(b) Controls that are within easy reach and clearly marked as to their use
and	func	tion?
		(c) Anti-skid walkway surface:
	4.	Does the size of the operator inhibit his performance?
	5.	Do any safety hazards exist?
	6.	Does the forklift operate with any hazardous handling characteristics?
	7.	Does the sound level result in unusual operator fatigue after prolonged
oper	ration	?
	8.	Is any special training required for:
		(a) Operators?
		(b) Maintenance personnel?
M.	Mar	uscripts, Manuals, Tools, and Test Equipment (User Comments):
	1.	Were operator, maintenance, and parts manuals furnished with the item of
equi	ipme	nt?
	2.	Are technical bulletins provided periodically by:
		(a) Dealer:
		(b) Manufacturer:
	3.	Do you use the commercial manual as supplied by the manufacturer/dealer
or s	pecif	y particular format and material? Have any difficulties been encountered in
usin	g the	manuals as a reference in the following areas:
		(a) Operating/setup instructions?
		(b) Servicing instruction?
		(c) Adjustments?
		(d) Repair and Maintenance?
trou	4. iblesl	Are special tools required by operators or mechanics to maintain or test/ noot any portions of the equipment? If so:
		(a) Are special tools provided by the manufacturer?
		(b) Are special tools described in the manual?

	(c) Is the use of special tools sufficiently described in the operator/repair
manu	1?
N. 7	raining and Logistic Support (User Data):
1	Are dealer repairs effected on a timely basis?
2	Do you experience any difficulty in training operator and/or maintenance
person	nel?
3	Is timely technical assistance available when required:
	(a) From the Dealer?
	(b) From the Manufacturer?
4	Would you purchase like additional and/or replacement items? If not, why?
	Analog State of Cook to Rock to reach the first state of the cook
.comn	Do you attempt to standardize makes and/or models of equipment/
ϵ	What is the length of warranty in equipment hours/months?
7	What is the total number of warranty claims?
8	Are delays frequently caused by the lack of timely receipt of repair parts?
9	What repair parts do you keep on hand for this item? If none stocked, why?
10 dealer	What is the length of time to fill emergency orders when parts are not in stock?
11 stock?	

APPENDIX B

COMPILED RESULTS FROM SURVEY OF INDUSTRIAL FORKLIFT USERS

- B-1. Compiled Results from Survey of Users of 4000- to 5000-Pound-Capacity Forklift Trucks
- B-2. Compiled Results from Survey of Users of 5000- to 5500-Pound-Capacity Forklift Trucks
- B-3. Compiled Results from Survey of Users of 6000- to 8000-Pound-Capacity Forklift Trucks

B-1. COMPILED RESULTS FROM SURVEY OF USERS OF 4000- TO 5000-POUND-CAPACITY FORKLIFT TRUCKS

-	1. Manufacturer	Clark	Clark	Clark	Towmoter	Towmotor	Towmotor	Towmotor	Hyster
	Model No.	C30040	C300-50	C500 40	T40B	T40B	T50B	T50B	S50C
	Date Purchased	Apr 77		69-73	Oct 75	71-76	71-76	Oct 75	16-77
	Capacity (lb)	4000	4450	4000	4000	4000	2000	2000	2000
	Load Center (in.)	24	24	24	24	24	24	24	24
	Tires	SRT	SRT	SRT	SRT	SRT	SRT	SRT	SRT
7.	2. Procurement Procedure	Unk							
	User Specification		×						×
	Sole Source					×	×		
	Competitive Bid		×	×	×			×	
	Dealer Recommendation								
	Manufacturer Recommendation								
	From Commercial Brochure								×
	Other			Past Performance		Past Experience	Past Experience		Past Experience
	Vehicle Purchased:				٠				
	New	×		×	×	×	×	×	*
	Used								
	Vehicles Leased		×						
3.	3. Components and Accessories	ies							
	Engine Manufacturer	TCM*	TCM	Waukesha	TCM	TCM	TCM	TCM	TCM
	Engine Model	F163	F163	D176	F163	F163	F163	F163	Unk
	Governor Type	Unk	Centrifugal	Vacuum	Mech Fly- Weight	Centrifugal	Centrifugal	Mech Fly- Weight	Mechanical
	Air Cleaner Manufacturer	Fram	Fram	Unk	United 2-stage	United 2-stage	United 2-stage	United 2-stage	Donaldson single-stage

* TCM - Teledyne Continental Motor

	PCV System	Yes	Yes	Yes	Yes	No	No	Yes	No
	Cooling System Capacity (C	£,			•		:		;
	Pressure (lb/in²)	Std	7	7	141	14	14.		Std
	Oil Filter Manufacturer	Clark	Fram	Clark	Unk	Cat	Cat		Wix
	Battery Model Clark Voltage Unk Capacity (amp) Unk	Clark Unk Unk	Clark 12 45	Clark 12 45	Quaker Unk Unk	Cat 12 67	Cat 12 67	Cat Unk Unk	Std 12 Unk
	Alternator Manufacturer	Delco	Delco	Delco	Delco		Delco		Delco
	Starter Manufacturer	Delco	Delco	Delco	Delco	Delco	Delco	Delco	Delco
4	4. Power Train								
	Transmission Manufacturer	Clark	Clark	Clark	Unk	Cat	Cat	Unk	Hyster
	Front Axle Manufacturer	Clark	Clark	Clark	Cat	Cat	Cat	Cat	Hyster
S	5. Steering & Brakes								
	Power Steering Furnished	Yes		Yes	Yes	Yes		Yes	Yes
	Steering Pump Separate from Hydraulic Pump	No No	No	No	Yes	Yes	Yes	Yes	Yes
	Power Steering Pump Manufacturer	Std	Vickers	Vickers	Std	Unk	Unk	Std	Std
	Power Steering Control Unit Manufacturer	Unk	Unk	Vickers	Unk	Saginaw	Saginaw	Unk	Std
	Power Brake Furnished	No	No	No	No	No	No	No	°N
	Brake Valve Manufacturer	Unk		Clark	Unk	Wagner	Wagner	Unk	Std
6	6. Hydraulic System								
	Filter Manufacturer	Unk	Unk	Clark	Unk	Purolator	Purolator	Unk	Unk
	Main Pump Manufacturer	Vickers		Vickers	Unk	Borg-Warner	Borg-Warner	Unk	Std
7.	7. Mast Assembly								
	Mast Type	Roller	Roller	Roller	Roller	Roller	Roller	Roller	Roller
	No. of Mast Stages	2	3	3	2	3	3	2	7

Sideshift	No	No	Yes	Yes	Yes	Yes	Yes	Yes
Sideshift Manufacturer	N/A	N/A	Clark	Cat	Towmotor	Towmotor	Cat	Unk
8. Instruments, Gauges, and Safety Devices	Safety Devices							
Hourmeter	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Ammeter	Gauge	Gauge	Gauge	Gauge	Gauge	Gauge	Gauge	Gauge
Engine Coolant Temp	Gauge	Gauge	Gauge	Gauge	Gauge	Gauge	Gauge	Gauge
Engine Oil Pressure	Light	Light	Gauge	Gauge	Gauge	Gauge	Gauge	Gauge
Fuel Gauge	Yes (LPG)	Yes (LPG)	Yes (LPG)	Yes	Yes	Yes	Yes (LPG)	Yes
Transmission Pressure Indicator	°N	°N	°N	No O	Light	Light	No No	^o Z
Transmission Temp Indicator	°N	% S	Light	No	oN.	Š.	No.	Gauge
Keyed Ignition Switch	Yes	Yes	Yes	Yes	Some	Some	Yes	Yes
Rear-View Mirror	No	No No	No	No	No	No	No	No No
Overhead Guard	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Load Backrest	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No No
Horn	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Floodlight (Number)	No	No	Yes (2)	No	Yes (2)	Yes (2)	No	No No
Taillight	No	No	No	No	No	No	No	No
Directional Lights	No	No	No	No	No	No	No	No No
Parking Brake	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Tilt Cylinder Anti- Cavitation Valve	Std	Yes	Yes	Std	Std	Std	Std	Std
Neutral Start Switch	Yes	Yes	Yes	No	Yes	Yes	No	N _o
9. What Optional Equipment is Utilized	t is Utilized							
Sideshift	No	No	Yes	No	Yes	Yes	Yes	Most Truc
Retractable Overhead Guard	°Z	°Z	o _N	No O	No No	Yes	No No	ç
Attachments (Clamps, etc)	No	Carpet Rams	. ulpak	Carton Clamp	Carton Clamp Roll Clamp	Carton Clamp Roll Clamp	Unk	Roll Clam
Special Lights	No	No	N _o	No	No	No	No	Yes

10. Functional Performance an	and Characteristics							
Geographical Location	Tenn	Fla	Fla	Ark	Ohio	Ohio	Ark	Oreg
Approx Time Operated Outdoors (%)	50	40	None	2	20	20	S	10
Is Truck Stored Out- doors in Cold Climate	No	No	No	No No	No	No	No	No.
Is Truck Difficult to Start in Cold Weather	N/A	N/A	No	°N	Yes	Yes	No V	N/A
Is truck operated in any other environmental locations	Unk	Unk	Cold Storage	°N	Sand Soda Ash	Sand Soda Ash	No No	Yes
Is truck exposed to environmental con- ditions (rain, dust, etc)	o N	Rain	Dust	No No	Dust	Dust	S S	Particle Board Plant
Did truck perform properly under these conditions	N/A	Yes	Overheated	N/A	Yes	Yes	N/A	Yes
What precautions taken to ensure acceptable operations	N/A	Caution for wet slick spots	Clean out radiator	N/A	Clean radiator each shift	Clean radiator each shift	N/A	Increased PN
11. Life-Cycle Information								
Date put in service	Apr 77	16-77	69-73	Oct 75	71-76	71-76	Oct 75	92
Expected annual usage (hr)	1200	720	3000	1800	3240	3240	1800	2000
Expected time between major overhauls (hr)	Unk	Unk	Unk	Unk	10,000 to 13,000	10,000 to 13,000	Unk	6000 to 8000
Expected life of the truck	Unk	Unk	21,000 hrs	12,600 hrs	10 уг	10 yr	7 yr	8 yr
12. Characteristics:								
Does engine operate on unleaded fuels	No (LPG)	No (LPG)	No (LPG)	No (LPG)	No (LPG)	No (LPG)	No (LPG)	No (LPG)
Is fuel filter provided	N/A	No	No	No No	No No	No	Unk	With LPG System
Capacity of fuel tank (lb)	36	33%	7.5	Unk	38	38	Unk	Unk
Ambient air Temp (°F)	Unk	18 to 100	80 to 95	Unk	-10 to 90	- 10 to 90	Unk	Unk
Air Cleaner System	Unk	Dry	Dry	Dry	Dry	Dry	Dry	Dry

Restriction Indicator	Unk	No	No	No	No	No No	No	Yes
Location of Air Intake	Engine comp	Side	Side	Outside	Under seat	Under seat	From	Under hood
Does the Drive Train contain the Following Components:	tne rollowing Cor	nponents:						
Torque Converter	Yes	Yes	Yes	No	No	No	No	No No
Power Shift Transmission	Yes	Yes	Yes	No O	No	No No	No	No No
Hydrostatic Transmission	No.	N _o	No No	°N	Yes	Yes	Š.	No.
Differential	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Positive Inching	Std	Yes	Yes	o _N	Yes	Yes	No	Unk
External Transmission Filter	Yes	Yes	Unk	No	yes	Yes	No O	Unk
Water Cooler for Transmission	Yes	Yes	Yes	No	°Z	°N _o	No No	o _N
Universal Joint Drive Shaft	No ON	No	No O	Yes	Yes	Yes	Yes	Yes
13. Electrical System:								
Protected by: Circuit Breakers								
Fuses	Fuses	Fuses	Fuses	Fuses	Fuses	Fuses	Fuses	Fuses
Alternator Furnished	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
14. Compatibility with Related Equipment:	ed Equipment:							
Transportation: Any difficulties in moving this truck to any job site	N/A	°Z	°Z	Š.	No	No.	0 V	N/A
What kind of equipment is used to transport this truck	None	Flatbed	Flatbed	Shop-built trailers	Vans flatbeds	Vans flatbeds	Shop-built trailers	None
Are lifting and/or tiedown attachments provided for ease of shipment	Unk	Yes	Yes	ů.	°N	N _O	o _N	Unk
Have any difficulties been encountered	Unk	None	None	None	None	None	None	Unk

Service Equipment: What special tools are required for servicing this truck	N/A	N/A	None	12-pt socket to remove U-joints	Tool for differential	Tool for differential	12-pt socket to remove U-joints	Unk
What special equipment other than special tools is required for this truck	None	None	For rebuild of trans	None	Floor lifts	Floor lifts	None	None
Have any difficulties been encountered using the various tools required for this truck	N/A	N/A	°Z	°Z	°Z.	°Z	°Z	°Z
15. Physical Characteristics:								
Length w/Forks (in.) w/o Forks (in.)	123% 80	128.6 84.6	130-3/8 88-3/8	124 83.5	130 82	134 86	131 87.5	125 83
Width (in.)	42	41.5	43.5	38	43	43	43	38
Overhead Guard Ht. (in.)	83	83	82.8	81	81.5	83	81	8.67
Collapsed Mast Ht. (in.)		83	103	N/A	83	83	N/A	70
Max. Fork Ht. (in.)	130	189	232	130	187	192	130	151.5
Free Lift (in.)	16	62.5	80.0	16	48	53	16	21.5
Backrest Ht. (in.)	48	48	48	48	48	48	48	47.9
Tilt Forward (degrees) Rearward (degrees)	6 10	4.0	40	6 12	4.0	m 2 0	6 12	6 12
Sideshift (in.) Left Right	N/A A/A	N/A N/A	44	44	44	44	44	44
Carriage Width (in.)	38		40	38	37	42	38	42.9
Fork Diemnsions (in.) Length Width Thickness	42 5 1-7/8	8 5 2	447	38.5 6 1.5	48 5 1.75	48 5 1.75	43 6 1.5	42 5 1.5
Do the forks comply with ANSI MH 11.4 (Hook-Type Mount)	Yes	Yes	Yes	Unk	Yes	Yes	Unk	Cink
Fork Adjustment								
Minimum (in.) Maximum (in.)	10 35	10 36	8 36	18 36	16 48	16 48	19% 33%	Chk Chk
Seat Clearance to	38-3/8	39	40	38	40.5	40.5	38	Unk
Underside of Over- head Guard (in.)								

Wheel Base (in.)	53	53	55	52	52	98	55	51
Drive Tire Tread Width (C to C) (in.)	33%	33	34.5	32	32	32	31	Unk
Steer Tire Tread Width (C to C) (in.)	321/4	32	32	33	33	33	33.5	Unk
Drive Tire Size	18 x 8 x 12-1/8	18 x 8 x 12.1	18 x 9 x 12.5	18 x 9 x 12-1/8	18 x 7 x 12.5	18 x 8 x 12.5	18 x 7 x 12-1/8	Unk
Number	2	2	2	2	2	2	2	Unk
Steer Tire Size	18 x 5 x 12-1/8	18 x 5 x 12.1	18 x 5 x 12.5	18 x 5 x 10.5	16 x 5 x 10.5	16 x 5 x 10.5	18 x 5 x 10.5	Unk
16. Reliability, Availability, and Maintainability Characteristics:	d Maintainability	Characteristics:						
General Data:								
Normal Workday in Clock-Hours	12	∞	24	∞	24	24	∞	∞
No. of shifts per day	1.5	1	3	1	3	3		1-3
Total no. of malfunctions requiring corrective maintenance	None	N/A	25/day	Unk	17 per day (76 trucks)	rucks)	Unk	Unk
Total clock-hours expended to perform corrective maintenance	N/A	N/A	6	Unk	14 per day (76 trucks)	rucks)	Unk	Unk
Total man-hours expended to perform corrective maintenance	Unk	Unk	45 per day	Unk	Unk	Unk	Unk	Chr
Organizational	None	Unk	All	ΑII	All	All	ЧΠ	All
Dealer	ΑII	Unk	None	None	None	None	None	None
Average down time awaiting parts not in stock at dealer location	N/A	Unk	None	Very little	24-48 hr	24-48 hr	Very little	Unk
Any particular systems or component failures (trend) contributes more to non-availability	N/A	N/A	None	Clutches Gaskets	Masts	Masts	Clutches Gaskets Burnt Valves	None
Do special tools, repair parts, technical assistance, inadequacies in maint or parts pubs contribute more to nonavalability	NA	N/A	°,	%	Š.	⁸	8	ž

ON ON		Checks fluid None levels	All other All	No No	No Yes, Part availability	°N N	°N °N	No No	No Changed location of oil filter; installed full-flow type	Unk No
ov ov		Clean radiators with air; perform PM check each shift	Everything except turn crankshafts	Replaces slider masts with roller masts	°Z °Z	Yes—Hydrostatic foot pedal when first used takes time to coordinate with accelerator	Yes-Modified transmission control linkage in Servo Assembly	No No	Modified transmission to be towed	Changing to roller masts
8		Checks fluid levels	All other	No	Ŷ.	Ŷ	°Z	No	2	Unk
_S		None	II V	Yes. Alter- nator, starter carburetor coil ignition wires at rebuild	8	°Z	Yes, uprights	No	°Z	Upright height in- creased to
° N	the:	None	Dealer per- forms all maint	No	No	Yes-Inching pedal & accelerator too close together	°N	No	N N	°Z
°,	is performed by	Checks fluid levels	Dealer performs all	Unk	o _N	°Z	° C	No	N N	Unk
Is non-availability contributed to by design deficiency or the need for a modification?	What type of maintenance is performed by the:	Operator	Mechanics	Are any components replaced on a scheduled basis? If so, what components and what interval:	Are you dissatisfied with any features of the equipment or your relationship with the manufacturer or dealer (specify)?	Are there any undesirable or unsatisfactory operating characteristics associated with this equipment (specify)?	Since purchasing the truck have there been any modifications of a corrective or improvement nature made by manufacturer?	Dealer	In-house	Is the user aware of any significant design changes to this model

Yes	Yes	Yes	Š.	&
d Yes	Yes	Yes	è	°
No. Ctrweight must be removed to replace water pump, belts hard to replace	ž	Yes	Yes, hard starting, LPG- fueled trucks when temp is below 20°F	Yes, Replacing water Pump & belts
No. Ctr to repla hard to	8	Yes	Yes, har fueled the temp is	Yes, Re
Yes	Yes	Yes	Š	&
Yes	Yes	Yes	Š	ο _ν
N/A	N/A	N/A	°Z	N/A
N/A	N/A	N/A	N/A	N/A
Are items requiring periodic maintenance accessible?	Can components be replaced and adjusted with minimum drainage and/or disturbance to other components?	Can maintenance be performed with conventional general purpose tools normally associated with this type of equipment?	Are there any problems resulting from extreme weather conditions such as cold starting difficulties, entrance of rain water into the operating components, etc.?	Are there any known maintenance tasks that are unduly difficult or time consuming that contribute to non-availability?

17. Scheduled Maintenance:

Indicate the interval and average time required for one man to perform each of the following maintenance operations:

			men to perform the topowing manifestation operations	and damped and	utchance operat	Marie.		
Replace Filters: Engine Oil Time	Monthly Unk	Unk N/A	200 hr 5 min	400 hr 5 min	28 days 10 min	28 days 10 min	900 hr 5 min	3 weeks
Air	Monthly	A/N	200 hr	500 hr	28 days	28 days	500 hr	None set
Time	Unk	A/N	5 min	5 min	5 min	5 min	5 min	Unk
Fuel	Monthly	N/A	As needed	As Needed	28 days	28 days	As needed	None set
Time	Unk	A/A	5 min		10 min	10 min	Unk	Unk
Transmission	Monthly	A/N	200 hr	As needed	28 days	28 days	As needed	None set
Time	Unk	A/N	5 min	Unk	10 min	10 min	Unk	Unk
Hydraulic	Unk	A/N	500 hr	700 hr	28 days	28 days	700 hr	None set
Time		A/N	30 min	15 min	30 min	30 min	15 min	Unk
Drain & Refill:								
Engine Oil	Monthly	N/A	200 hr	450 hr	28 days	28 days	450 hr	3 wk
Time	Unk	N/A	10 min	20 min	20 min	20 min	20 min	10 min

None set Unk	None set Unk	None set 10 min	3 wk 30 min	None	None	2 hr			45	45	10	10	10	120	240		o _N		No
900 hr 25 min	1500 hr 30 min	Annually 15 min	450 hr 30 min	Complaints only	Unk	Unk			35	35	20	10	09	150	120		Yes		No
None Unk	None Unk	Annually 15 min	28 days 20 min	10 min/truck	1 hr/truck	4 hr/truck			15	09	15	15	30	120	360		No		No
None Unk	None Unk	Annually 15 min	28 days 20 min	10 min/truck	1 hr/truck	4 hr/truck			15	09	15	15	30	120	360		No O		No
900 hr 30 min	1500 hr 30 min	Annually 15 min	450 hr 30 min	Complaints only	Unk	Unk			35	35	20	10	09	150	120		Yes		No
As required 15 min	As required 30 min	As required 15 min	200 hr 60 min	9 hr/fleet	50 hr/fleet	200 hr/fleet		e and replace:	30	09	20	10	15	09	360		Yes		No
N/N A/N	N/A N/A	N/A A/A	N/N A/N	Unk	Unk	Unk		one man to remov	N/A	N/A	N/A	N/A	N/A	N/A	N/A	(8)	Yes	t during?	Yes Inching Pedal
Unk	Unk Unk	Unk	Monthly Unk	Unk	No records	N/A	Data:	min) required for	N/A	N/A	N/A	N/A	N/A	N/A	N/A	: (User Commen	o _N	hazards that exis	No
Transmission oil Time	Hydraulic Oil Time	Cooling System Time	Lubrication Time	Preventative maintenance Time: Man-hours expended for daily services (Av)	Man-hours Expended for Weekly Preventa- tive Maintenance Service (Av)	Man-hours Expended for Monthly Preventa- tive Maintenance Service (Av)	18. Component Replacement Data:	Indicate the average time (min) required for one man to remove and replace:	Alternator	Starter	Voltage Regulator	Battery	Fan Belt	Hydraulic Pump	Brake Shoes	19. Safety and Human Factors: (User Comments)	Do you augment the manufacturers safety precautions?	Do you know of any safety hazards that exist during?	Operation

Maintenance	N/A	No	No	No	No	No	No	No
Are the following safety and human-factors items/elements furnished as standard or optional equipment adequate?	nd human-factors	items/elements	furnished as standa	urd or optional equ	ipment adequate?			
Gauges and Monitors	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Controls within easy reach & clearly marked	Markings obliterated	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Anti-skid walkway surface	No	Yes	Yes	Yes	Not on all trucks	S	Yes	Yes
Does the operator's size inhibit his performance?	No No	N _o	°Z	N _o	No	No O	No	No
Do any safety hazards exist?	No	N _o	Š.	o _N	No	No	No	Š
Does the truck operate with any hazardous handling characteristics?	o _N	No	No	No	No	ON	o _N	No
Does the sound level cause operator fatigue after prolonged operation?	N _O	No V	°Z	°Z	No No	No	No ON	No
Is special training required for:	for:							
Operators?	No	No	No	No	yes 6 hr	yes 6 hr	No	No
Maintenance Personnel?	N/A	N/A	No	N _o	yes cat school	yes cat school	No	No
20. Manuscripts, Manuals, Tools, and Test Equipment (User Comments):	ols, and Test Equi	pment (User Co	mments):					
Were operator, maintenance, and parts manuals furnished with the item of equipment?	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Have any difficulties been encountered using the manuals as a reference in the following areas:	encountered usin	g the manuals a	s a reference in the	following areas:				
Operating/Setup Instructions	NA	No	°N	°N	°Z	°N	Š.	Yes
Servicing Instructions	N/A	N/A	No	No	No	No.	No	Yes
Adjustments	N/A	N/A	No	N _o	No	No	No	Yes
Repair and Maintenance	N/A	N/A	°N	°Z	Ŷ.	°N	° N	Yes

ž	N/A	N/A	N/A		Not always	°N		No	Yes	Yes, except for parts availability	Yes	90 days	Unk
ž	N/A	N/A	A/N		Yes	°Z		Yes	Unk	Yes	Yes	Unk	Unk
Yes	om the	Only in the service manual	No In the service manual only		Yes	^o Z		Yes	Yes	Yes	Yes	500 hr on engine 30 days parts & labor	Very few
Yes	Purchased from the manufacturer	Only in the	No In the se		Yes	No O		Yes	Yes	Yes	Yes	500 hr on eng parts & labor	Very few
Š	N/A	N/A	N/A		Yes	Š		Yes	Unk	Yes	Yes	Unk	Unk
Yes	Yes	Yes	Yes		Yes	N _O		Yes	Yes	Yes	Yes	500 hr or 90 days	v ₀
N/A	Unk	Unk	Unk		Yes	°Z	n required?	Yes	Yes	Yes	Yes	Leased	Unk
A/A	Unk	Unk	Unk	port:	Yes	o _N	nce available whe	Yes	Not required	Yes	Unk	Unk	None
Are special tools required by operators or mechanics to maintain or test/troubleshoot any portions of the equipment?	Are special tools provided by the manufacturer?	Are special tools described in the manual?	Is the use of special tools sufficiently described in the operator/repair manual?	21. Training and Logistic Support:	Are dealer repairs performed promptly?	Any difficulty in training operator and/or maintenance personne!?	Is timely technical assistance available when required?	From Dealer	From Manufacturer	Would you purchase additional and/or replacement items?	Do you attempt to standardize names and/or models of equipment/components within your fleet?	What is the length of warranty in equipment hours/months?	What is the total number of warranty claims?

Unk	Starters, clutches, trans	1 day to 3 wk	1 day to 3 wk
N _O	Clutches, belts, points, coil, plugs, valves	Less than 48 hr	Less than 48 hr
°Z	Everything except frame & masts	24 hr	48 hr
Š	Everything masts	24 hr	48 hr
°Z	Clutches, fanbelts, points, valves, plugs	Less than 48 hr	Less than 48 hr
°N N	Almost all parts stocked	48 hr	10-15 days
No	None; dealer performs all maint	Unk	Unk
Unk	None; dealer performs all maint	Unk	Unk
Are delays frequently caused by the lack of timely receipt of repair parts?	What repair parts do you keep on hand for this item? If none stocked, why not?	What is the length of time to fill emergency orders when parts are not in dealers stock?	What is the length of time to fill normal orders when parts are not in dealers stock?

B-2. COMPILED RESULTS FROM SURVEY OF USERS OF 5000- TO 5500-POUND-CAPACITY FORKLIFT TRUCKS

-	1. Manufacturer	Hyster	Clark	Clark	Hyster	Clark	Towmotor	AC
	Model No.	S50C	C500-50	CS00-50	S50C	C500-55	TSSB	ACC55
	Date Purchased		91-99	72	92	69-73	76	73-74
	Capacity (lb)	2000	2000	2000	2000	5500	5500	9200
	Load Center (in.)	24	24	24	24	24	24	24
	Tires	SRT	SRT	SRT-Pneu	SRT	SRT	PNEU	SRT
7.	2. Procurement Procedure							
	User Specification	×						×
	Sole Source				×			
	Competitive Bid	×	×	×	X (depending on location)	*		×
	Dealer Recommendation						×	
	Manufacturer Recommendation							
	From Commercial Brochure				Generally, no			
	Other		Demo by dealers	Past history		Past per- formance		Own spec
	Vehicle Purchased: New Used	×	×	×	×	×	×	×
	Vehicles Leased			Yes	Short term only			
e.	3. Components and Accessories:							
	Engine Manufacturer	TCM*	Waukesha	Std	TCM	Waukesha	TCM	TCM
	Engine Model	Std	D-1766	Std	F-163	D-176	Std	AC 153
	Governor Type	Mechanical	Centrifugal	Centrifugal	Std	Vacuum	Mechanical	Mechanical
	Air Cleaner Manufacturer	Std	Unk	Std	Std	Unk	United	United
	PCV System	Std	Yes	Yes	Std	Yes	Unk	No.
	Cooling System Capacity Pressure (lb/in ²)	Std Std	11 qt	10 qt Unk	Std Std	11 qt	Std Std	Std
•	* TCM - Teledyne Continental Motor							

Oil Filter Manufacturer	Std	Clark	Std	Std	Clark	Motorcraft	AC P3
Battery Model Voltage Capacity (amp)	Std 12 Std	Clark 12 Unk	Std 12 Std	Std 112 Std	Unk 12 45	Astrolite 12 55	Std 12 Std
Alternator Manufacturer	Std	Delco	Std	Std	Delco	Std	Delco
Starter Manufacturer	Std	Delco	Std	Std	Delco	Std	Delco
4. Power Train							
Transmission Manufacturer	Std Auto	Clark	Std	Std	Clark	Cat	Std
Front Axle Manufacturer	Std	Clark	Std	Std	Clark	Std	Std
5. Steering and Brakes							
Power Steering Furnished	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Steering Pump Separate from Hydraulic Pump?	Yes	Yes	Unk	Yes	o _N	Unk	Š
Power Steering Pump Mfgr	Std	Vickers	Std	Std	N/A	Unk	N/A
Power Steering Control Unit Std Clark Manufacturer	Std	Clark	Std	Std	Vickers	Std	Std
Power Brake Furnished	No	No	Unk	Yes	No	Unk	No.
Brake Valve Mfgr	Std	Clark	Std	Std	Clark	Unk	Std
6. Hydraulic System							
Filter Manufacturer	Std	Clark	Std	Std	Clark	Std	Std
Main Pump Manufacturer	Std	Vickers	Std	Std	Vickers	Std	Std
7. Mast Assembly							
Type	Roller	Roller	Roller	Roller	Roller	Roller	Roller
No. of Mast Stages	3	3	3	3	3	2	2
Sideshift	Yes	Yes	No	No	Yes	No	Yes
Sideshift Manufacturer	Cascade	Clark	N/A	N/A	Clark	N/A	Unk
8. Instruments, Gauges, and Safety D	evices						
Hourmeter	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Ammeter	Gauge	Gauge	Gauge	Light	Gauge	Gauge	Gauge
Engine Coolant Temp	Gauge	Gauge	Gauge	Light	Gauge	Gauge	Gauge

Engine Oil Pressure	Gauge	Gauge	Gauge	Light	Gauge	Gauge	Gauge
Fuel Gauge	LPG	Yes	LPG	LPG	LPG	LPG	Yes
Transmission Pressure Indicator	Unk	No	No	No	No	No	No
Transmission Temp Indicator	Unk	No	No	No	Light	No	Light
Keyed Ignition Switch	Yes	Yes	Yes	Yes	Yes	No	Yes
Rear-View Mirror	No	No	No	No	No	No	No
Overhead Guard	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Load Backrest	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Ноги	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Floodlight (Number)	Yes; user installed	Yes; user installed	No O	No	Yes (2)	No	Š
Taillight	Yes	No	No	No	No	No	No.
Directional Lights	No	No	No	No	No	No	S _o
Parking Brake	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Tilt Cylinder Anticavitation valve	Yes	Yes	Unk	Yes	Yes	Yes	Std
Neutral Start Switch	Yes	Yes	Yes	Yes	Yes	No	Yes
Starter Disconnect	Unk	Yes	Yes	Yes	Yes	Unk	No
9. Optional Equipment Used:							
Sideshift	Yes	Yes	No	No	Yes	No	Yes
Retractable Overhead Guard	No	Yes	Yes	No	No	No	No
Attachments (Clamps, etc.)	Push-pull attachment	Clamps, pull pack	None	Yes	Clamp, pull pack	No	Yes
Special Lights	Revolving caution	No No	Revolving caution	Revolving caution	N _o	Yes	None
10. Functional Performance and Characteristics	cteristics						
Geographical Location	Nationally	Fla	Ohio	Ohio	Fla	Colo	Wash
Approx Time Operated Outdoors	Very little	2%	20%	None	None	2%	10%
Is truck stored outdoors in cold climate?	No O	N/A	Sometimes	No O	No	No	Š
Is truck difficult to start in cold weather?	N/A	No	Yes	No	o _N	No	No.

Is truck operated in any other environmental locations?	Yes-Refinery	Yes-Cold Storage	o _Z	No	Yes-Cold Storage	Š.	No
Is truck exposed to unusual environmental conditions (rain, dust, etc.)?	Yes	Freezers, Mill	°Z	No.	Dust	N O	No O
Did truck perform properly under these conditions?	Yes	Yes	N/A	N/A	Overheated	N/A	N/A
What precautions are taken to ensure acceptable operation?	None	Clean radiator frequently	N/A	N/A	Clean radiator frequently	N/A	N/A
11. Life Cycle Information:							
Expected Annual Usage (hr)	1600	4000	4-5000	2500	3000	4000	2000
Expected Time Between Major Overhaul (hr)	6000 to 8000	12,000	Unk	No overhaul	Unk	Unk	Depends on where used
Expected Life of the Truck	6 уг	20,000 hr	5 yr	10,000 to 15,000 hr	21,000	Unk	7 yr
12. Characteristics:							
Does engine operate on unleaded fuels?	No. LPG	No. LPG	No. LPG	No. LPG	No. LPG	No. LPG	No. LPG
Is fuel filter provided?	Unk	No	No	No	No	Unk	No
Capacity of fuel tank	33½ lb	7.7 gal	35 lb	33½ lb	75 Ib	43.5 lb	Unk
Ambient Air Temperature Range	Varies as to location	40° to 100°F	Unk	Unk	80° to 95°F	Unk	Unk
Air Cleaner System	Dry	Dry	Dry	Dry	Dry	Dry	Dry
Restriction Indicator	No	No	No	Yes	No O	Yes	Yes
Location of Air Intake	Under hood	Side	Under hood	Under hood	Side	Through hood	Inside engine comp.
Does the drive train contain the following components:	llowing components						
Torque	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Power Shift Transmission	Yes	Yes	Yes	Yes	Yes	No	Yes
Hydrostatic Transmission	No	No	No	No	No O	Yes	No
Positive Inching	Unk	Yes	Yes	Yes	Yes	No.	No
External Transmission Filter	Std	Yes	Yes	Yes	Unk	Unk	No
Water Cooler for Transmission	Unk	Yes	Yes	Yes	Yes	Yes	Yes
Universal Joint Drive Shaft	Std	No	Yes	No.	No	Yes	No

13. Electrical System

Protected by: Circuit Breakers		2	Poth	Filese	Fuses	Fuses	Fuses
Fuses	ruses	ruses	mon				7.7
Alternator Furnished	Yes	Yes	Yes	Yes	Yes	Yes	res
14. Compatibility with Related Equipment	nent						
Transportation:							
Any difficulties in moving this truck to any job site?	Not transported	No O	No	No	° N	No V	Yes
What kind of equipment is used to transport this truck?	N/A	Tilt bed trailer	Comm. carrier	Semi-trailer flat bed unit	ed unit	N/A	Low profile trailer
Are lift and/or tiedown attachments provided for ease of shipment?	N/A	Yes	Unk	Tiedowns	Yes	V/N	o _N
Any difficulties been encountered using these tiedowns?	N/A	None	Unk	Shifting of truck	None	V/A	N/A
Service Equipment:							
What special tools are required for servicing this truck?	None	Clutch alignment tool	N/A	None	None	None	None
What special equipment other than special tools is required for this truck?	None	None	Tubing wrench	None	Required, type Unk	None	None
Have any difficulties been encountered using the	N/A	N/A	No No	N/A	°Z	N/A	N/A
this truck?							
15. Physical Characteristics							
Length w/Forks (in.) w/o Forks (in.)	125 83	130-3/8 88-3/8	133.3 88.3	116 to 146 86.0	130-3/8 88-3/8	146 102	127 83.5
Width (in.)	38	43.5	43	41	43.5	47.5	42
Overhead Guard Ht (in.)	79.8	82.88	82.9	82.6	82.8	88	62
Collapsed Mast Ht (in.)	70	83.0	82.9	83.0	103	76.5	78.5
Max. Fork Ht (in.)	151.5	187	187	187.5	232	106	Unk
Free Lift (in.)	21.5	62.6	62	33.5	08	20	Unk
Backrest Ht (in.)	47.9	48.0	48.0	48.2	48	48	Std

Tilt Forward (degrees)	9	•	9	9	4	Std	Std
Rearward (degrees)	12	9	10	12	9	Std	Std
Sideshift (in.) Left Right	44	44	N/A	N/A	44	N/A	25
Carriage Width (in.)	42.9	37	43	36	40	45%	38.5
Fork Dimensions (in.) Length Width Thickness	42 5 1.5	42 5.5 1.75	42 5.5 1.75	30-60 5.0 1.5	440	42 5 1-7/8	1.5
Do the forks comply with ANSI MH11.4 (hook-type mount)?	Yes	Yes	Unk	Unk	Yes	Yes	Yes
Fork Adjustment Dimensions: Minimum (in.) Maximum (in.)	10 35	10 36	10 36	10 35	36	10	8.5
Seat Clearance to Underside of Overhead Guard (in.)	Unk	40	39.5	39.0	40	39	37
Wheel Base (in.)	51	55	53	51.0	55	66.5	49.5
Drive Tire Tread Width (C to C) (in.)	32.0	34.5	34.5	32	34.5	39%	31.5
Steer Tire Tread Width (C to C) (in.)	34.0	32.0	32.0	34	32	34%	33
Drive Tire Size	18 x 9 x 12.1	18 x 9 x 12.12	Std	18 x 9 x 12.1	18 x 9 x 12.5	8.50 x 15	Std
Number	2	2	2	2	2	2	7
Steer Tire Size	16 x 6 x 10.5	18 x 5 x 12.12	Std	16 x 6 x 10.5	18 x 5 x 12.5	650 x 10	Std
16. Reliability, Availability, and Maintainability Characteristics	ainability Characte	ristics					
General data:							
Normal workday in clock-hours	80	10-24	24	24	24	15-18	00
Number of shifts per day	1	2	3	3	3	3	_
Total number of malfunctions requiring corrective maintenance	Unk	12/day per fleet	3	2	25/day per fleet	3	Unk
Total clock-hours expended to perform corrective maintenance	Unk	6/day	2 to 6	-	9/day	Unk	Unk

Total man-hours expended to perform corrective maintenance	Unk	40/day	2-6/day	Unk	45/day	Unk	Unk
Organizational	All except leased trucks	АШ	PM only	ΑIJ	All	All except eng/trans	All except trans
Dealer	None except all maint on leased trucks	None	All	None	None	Eng/trans only	Trans only
Average downtime awaiting parts not in stock at dealer location	Very little	3 days	i-10 days	No require- ment; new truck	None	No problem	14 days
Any particular systems or component failures (trend) contributes more to nonavailability	Unk	None	Carburetor inching	Uprights	N/A	N/A	Major engin parts
Do special tools, repair parts, technical assistance, inadequacies in maintenance or parts availability contribute more to non-availability?	Unk	°Z	Š	Repair parts	°Z	°Z	°Z
Is non-availability contributed to by design deficiency or the need for a modification?	Unk	No	Unk	No	N _o	No No	%
What type of maintenance is performed by the:	rmed by the:						
Operator	None	Service check	None	Check fluid levels	None	None	None
Mechanics	All maint	All other	Routine PM	All other	All maint	All maint	All maint
Are any components replaced on a scheduled basis? If so, what components and what interval?	No No	°N	N _O	°Z	°N	ON.	°N
Are you dissatisfied with any features of the equipment or your relationship with the manufacturer or dealer? (Specify)	S.	°Z	Yes. Electrical wire to use in explosive areas.	Yes; want better visibility	0 V	°Z	o _N
Are there any undestrable or unsatisfactory operating characteristics associated with the equipment? (Specify)	0 N	°Z	o _N	Yes; visibility	None	Yes; runs hot. Hand brake works impro- perly.	°Z

Since purchasing the truck have there been any modifications of a corrective or improvement nature made by:

	Manufacturer	No V	No O	o _N	Š	Yes; uprights	Yes. Moved radiator back 1/4 in.	°N
	Dealer	No	No	No	No O	No O	No	No
	In-House	No	Installed lights	Installed lights	No	No	No	No
	Is the User aware of any significant design changes to this model truck in the last year?	N O	N _O	Ŷ.	Yes	Yes; uprights increased to 240 in.	N _O	Yes. Using continental engine
	Are all items requiring periodic maintenance accessible?	Yes	No No	Yes	No	Yes	Yes	Yes
9	Can components and accessories be replaced and adjusted with a minimum drainage and/or disturbance to other components?	Yes	Yes	No; front brakes	ê.	Yes	Yes	Yes
J	Can periodic maintenance be performed with general-purpose tools normally associated with this type of equipment?	Yes	Yes	N O	Yes	Yes	Yes	Yes
	Are there any problems resulting from extreme weather conditions such as cold starting difficulties, entrance of rain water into the operating components, etc.?	°Z	8	Yes	_Q	ο <mark>ν</mark>	, Q	o Z

17. Scheduled Maintenance

Indicate the interval and average time required for one man to perform each of the following maintenance operations:

iltore
-
9

Hydraulic Time	250 hr Unk	6 mo 30 min	300 hr 30 min	1000 hr 60 min	500 hr 30 min	Unk	1200 hr Unk
Drain & Refill:							
Engine Oil Time	100 hr Unk	60 hr 30 min	300 hr 30 min	200 hr 10 min	200 hr 10 min	300 hr 30 min	200 hr Unk
Transmission Oil Time	500 hr Unk	12 mo 30 min	1200 hr 30 min	1000 hr 15 min	As required 15 min	2000 hr Unk	1200 hr Unk
Hydraulic Oil Time	Unk	6 mo 30 min	1200 hr 30 min	1000 hr 15 min	As required 30 min	As required Unk	1200 hr Unk
Cooling System Time	As required Unk	As required 30 min	When needed 15 min	As needed 10 min	As required 15 min	Never N/A	2400 hr Unk
Lubrication Time	100 hr Unk	60 hr 30 min	300 hr 20 min	200 hr 10 min	200 hr 60 min	300 hr 60 min	200 hr Unk
Preventative Maintenance Time:							
Man-hours expended for daily servicing (Av.)	None	5 min	15 min	15 min	9 hr	5-10 min	5 min
Man-hours expended for weekly preventative maintenance service (Av.)	Unk	30 min	Unk	2 hr	50 hr (fleet)	Unk	Unk
18. Component Part Replacement Data	22						
Indicate the average time (min) required for one man to remove and replace:	uired for one man	to remove and repl	ace:				
Alternator	120	45	120	15	30	30	Unk
Starter	120	09	120	30	09	09	Unk
Voltage Regulator	10	15	09	30	20	30	Unk
Battery	10	15	09	10	10	20	Unk
Fan Belt	30	20	09	S	15	120	Unk
Hydraulic Pump	09	06	180	45	09	Unk	Unk
Brake Shoes	240	300	480	240	360	Unk	Unk
19. Safety and Human Factors (User Comments)	Comments)						
Do you augment the manu- facturer's safety precautions?	Yes	Yes ·	Yes	Yes	Yes	Yes	o _N
Do safety hazards exist during:							
Operation? Maintenance?	% % %	No. O	Visibility No	No No	No o	No o	°N N

Are the following safety and human-factors items/elements furnished as standard or optional equipment adequate?	n-factors items/ele	ments furnished as	standard or option	al equipment adequ	late?	
Gauges and monitors	Yes	Yes	Yes	Yes	Yes	Yes
Controls within easy reach and clearly marked?	Yes	Yes	Yes	Yes	Yes	Yes
Anti-skid walkway surface	Yes	Yes	Yes	Yes	Yes	Yes
Does the operator's size inhibit his performance?	oN O	No.	Š	No	No	N _o
Do any safety hazards exist?	No No	No	No	No	No	No
Does the sound level cause operator fatigue?	o _N	No.	S.	No	No	No
Is training required for: Operators	Yes, with new models	Yes	Yes	N _o	No OJT	Yes
Maintenance Personnel	Yes, with new models	Yes	Yes	No	No	oN.
20. Manuscripts, Manuals, Tools, and Test Equipment (User Comments)	Test Equipment (Jser Comments)				
Were operator, maintenance, and parts manuals furnished with the item of equipment?	Yes	Yes	Yes	Yes	Yes	Yes
Are technical bulletins produced periodically by:	eriodically by:					
Dealer? Manufacturer?	Unk	Yes Unk	% o	No ox	° ° °	Unk
Have any difficulties been encountered using the manuals as a reference in the following areas:	ered using the man	uals as a reference	in the following are	as:		
Operating; setup instructions?	No	No	No	No	No	No
Servicing instruction?	No	No	No	No	No	No
Adjustments?	No	No	No	No	No	No
Repair & maintenance?	No	No	No	No	No	No
Are special tools required by operators or mechanics to maintain or test/troubleshoot any portions of the equipment?	° N	Yes	Yes	Yes	Yes	°Z
Are special tools provided by the manufacturer?	N/A	No	No	Yes	Yes	N/A
Are special tools described in the	N/A	Yes	No	Yes	Yes	N/A

Is the use of special tools adequately described in the operator/repair manual? 21. Training and Logistic Support Are dealer repairs performed promptly? Any difficulty in training operator and/or maintenance personnel? Is technical assistance available whe From Dealer From Manufacturer	at tools N/A Ye bed in the tanual? stic Support Yes Ye raining No No anintenance to available when required from dealer? Yes No No No No No noter Yes No	Yes Yes No	No Yes Yes Yes	Yes Yes Yes	Yes Yes Yes Yes	N/A Yes Yes Yes Yes	N/A Yes
would you purchase like additional and/or replace- ment items? Do you attempt to standardize names and/or models of equipment/components within your fleet?	Yes	Yes	Yes Yes	Yes	Yes	Yes	Yes
What is the length of warranty in equipment hours/months? What is the total number of warranty claims?	Unk	90 days 500 hr Very few	1 yr	90 days 500 hr None	90 days 500 hr 5	6 mo	1 yr None
Are delays frequently caused by the lack of timely receipt of repair parts?	No	o _N	°Z	N _o	^o Z	°Z	N _o
What repair parts do you keep on hand for this item? If none stocked, why not?	More than average due to nature of operation	Just about everything	General tune-up parts	Minor repair parts	Just about everything	Gas regulators, starters, alternator	None
What is the length of the time to fill emergency orders when parts are not in dealers stock?	72 hr	1 wk	1-10 days	2-3 wk	10-15 days	3 days or less	48 hr

B-3. COMPILED RESULTS FROM SURVEY OF USERS OF 6000- to 8000-POUND-CAPACITY FORKLIFT TRUCKS

1. Manufacturer	Towmotor	Towmotor	Hyster	Hyster	AC	Hyster
Model No.	V60B	V60B	Э09Н	Э09Н	ACP70	H80C
Date Purchased	76	73-76	91-19	76	73-74	92
Capacity (lb)	0009	5000 to 6500	0009	7000	7000	8000
Load Center	24 in.	24 in.	24 in.	24 in.	24 in.	24 in.
Tires	Foam-filled	Pneu	Pneu	Pneu	SRT	Pneu
2. Procurement Procedure						
User Specification	×	×	×	×	×	×
Sole Source		×		×		
Competitive Bid	Price not prime concern	×	×		×	×
Dealer Recommendation			×		×	×
Manufacturer Recommendation			×		×	×
From Commercial Brochure		×	×	×		
Other	Company evaluation	Past performance		Past experience		Prefer Hyster
Vehicles Purchased:						
New Used	×	×	×	×	×	*
3. Components and Accessories						
Engine Manufacturer	TCM* Specified	Perkins	TCM	TCM	AC Diesel	TCM
Engine Model	F227	4.236	Unk	Unk	Unk	Unk
Governor Type	Centrifugal	Velocity	Mechanical	Mechanical	Std	Mechanical
Air Cleaner Manufacturer	Farr	Farr	Unk	Donaldson	United	Unk
PCV System	Yes	Yes	No	No	No	Yes
Cooling System Capacity Pressure (1b/in. ²)	20 qt	20 qt	Std Std	22 qt Std	Std Std	Std Std
Oil Filter Manufacturer	Purolator	Purolator	Std	Wix	Std	Std
* TCM - Teledyne Continental Motor						

Battery Model	Gould	Could	Std	Std	Std	Std
Voltage Capacity (amp)	12 67	12 172	12 Unk	12 Unk	12 Unk	12 Unk
Alternator Manufacturer	Delco Heavy-Duty	Delco Heavy-Duty	N/A	Delco	Delco	Std
Starter Manufacturer	Delco	Defco Enclosed	Std	Delco	Delco	Std
4. Power Train						
Transmission Manufacturer	Std Hydrostatic	Std Hydrostatic	St©	Hyster	Std	Std
Front Axle Manufacturer 5. Steering & Brakes	Towmotor	Towmotor	Std	Hyster	Std	Std
Power steering furnished?	Yes	Yes	Yes	Yes	Yes	Yes
Steering pump separate from hydraulic pump?	Yes	Yes	Yes	Yes	No	Yes
Power steering pump manufacturer	Eaton	Eaton	Std	Std	N/A	Std
Power steering control unit manufacturer	Ross	Ross	Std	Std	Std	Std
Power brake furnished?	No	No	Yes	No	No	Yes
Brake valve manufacturer	Wagner	Wagner	Std	Std	Std	Std
6. Hydraulic System						
Filter manufacturer	Walker	Walker	Std	Std	Std	Std
Main pump manufacturer	Borg-Warner	Borg-Warner	Std	Std	Std	Std
7. Mast Assembly						
Mast Type	Roller	Roller	Roller	Roller	Roller	Roller
Number of mast stages	Up to 4	1, 2, or 3	2	2	2	7
Sideshift	Yes	No	Yes	Yes	Yes	Yes
Sideshift manufacturer	Cascade	N/A	Unk	Unk	Unk	Unk
8. Instruments, Gauges, and Safety Devices						
Hourmeter	Yes	Yes	Yes	Yes	Yes	Yes
Ammeter	Gauge	Gauge	Light	Gauge	Gauge	Light

Engine Coolant Temperature	Gauge	Gauge	Light	Gauge	Gauge	Light
Engine Oil Pressure	Gauge	Gauge	Light	Gauge	Gauge	Light
Fuel Gauge	Yes	Yes	Yes	Yes	Yes	Yes
Transmission Pressure Indicator	No	No	No	No	No	Unk
Transmission Temp Indicator	No	No	No	Gauge	Light	Unk
Keyed Ignition Switch	Yes	Yes	Yes	Yes	Yes	Yes
Rear-view Mirror	No No	No	No	No	No	No
Overhead Guard	Yes	Yes	Yes	Yes	Yes	Yes
Load Backrest	Std	Yes	Yes	No OX	Yes	Yes
Horn	Std	Yes	Yes	Yes	Yes	Yes
Floodlight(s)	Yes (2)	Yes (2)	No	No	No	N _o
Taillight	Yes	Yes	No	No	No	No No
Directional Lights	No	No	S.	No	No	No
Parking Brake	Yes	Yes	Yes	Yes	Yes	Yes
Tilt Cylinder Anti-cavitation Valve	No	No	No	Std	Std	Std
Neutral Start Switch	Yes	Yes	No	Yes	Yes	No No
Starter Disconnect	Yes	Yes	No	No	No	No
9. Optional Equipment						
Sideshift	Yes	Yes	Yes	Yes	Yes	Yes
Retractable overhead guards	No	No	No	No	. oN	No
Attachments (clamps, etc)	Yes	No	No O	Roll Clamps	Yes	N _o
Special Lights	Yes	No	None	Flashing Amber	None	None
10. Functional Performance and Characteristics	83					
Geographical Location	La	Tenn	Wash State	Oreg	Wash State	Wash Sta
Approx Time Operated Outdoors (%)	100	86-09	90	10	50	20
Is truck stored outdoors in cold climate?	No	Yes	No	No	No	No
Is truck difficult to start in cold weather?	No	No	N/A	N/A	No	N/A
Is truck operated in any other environ- mental locations?	Heavy dust Furnace areas	Furnace areas	No	Yes	No	No

Is truck exposed to unusual environ- mental conditions (rain, dust, etc.)?	Heavy dust	Dust, rain, fly ash, foundry, sand	No	Particle Plant dust	No O	Š.
Did truck perform properly under these conditions?	Yes	Yes	N/A	Yes	N/A	N/A
What precautions are taken to ensure acceptable operation?	Farr Air Cleaners	Farr Dual-Stage Air Cleaners	N/A	Increased PM	N/A	N/A
11. Life-Cycle Information						
Expected annual usage (hr)	2100	0009	1000	2000	2000	1000
Expected time between major overhauls (hr)	10,000	12,000	Unk	8000	Unk	Unk
Expected life of the truck (hr)	10,000	40,000	5-7 yr	8 yr	7 yr	5-7 yr
12. Characteristics						
Does engine operate on unleaded fuels?	No	No, Diesel	No, LPG	No, LPG	No, Diesel	No, LPG
Fuel filter provided?	Yes	Yes	Std	Yes	Std	Std
Capacity of fuel tank	9.3 gal	9.3 gal	Unk	Unk	Std	Unk
Ambient air temperature	70-110°F	60-120°F	1	1	Í.	E.
Air cleaner system	Dry	Dry	Dry	Dry	Dry	Dry
Restriction indicator	Yes	Yes	Yes	Yes	Yes	Yes
Location of air intake	On overhead guard	On top of ctrwt	Inside engine compartment	Under hood	Inside engine compartment	Inside engi
Does the drive train contain the following components:	components:					
Torque converter	No	No	No	No	No	Yes
Power shift transmission	No	No	No	No	Yes	Yes
Hydrostatic transmission	Yes	Yes	No	No	No	No No
Differential	Yes	Yes	Yes	Yes	Yes	Yes
Positive inching	No	Yes	Yes	No	No	Yes
External transmission filter	Yes	No	No	No	No	Yes
Water cooler for transmission	Yes	Yes	No	No	Yes	Yes
Universal joint drive shaft	Yes	Yes	Yes	Yes	No	Yes

13. Electrical System

Protected by:						
Circuit breakers/fuses Alternator furnished	Fuses Yes	Fuses Yes	Fuses No (Generator)	Fuses Yes	Fuses Yes	Fuses Yes
14. Compatibility with Related Equipment						
Transportation						
Any difficulties in moving this truck to any job site?	Yes, hard to push or pull	Not transported	Not transported	Not transported	Yes	Not transported
What kind of equipment is used to transport this truck?	Larger FLT	N/A	N/A	N/A	Low-profile trailer	N/A
Are lifting and/or tiedown attachments provided for ease of shipment?	No	N/A	N/A	N/A	No	N/A
Have any difficulties been encountered?	As stated	N/A	N/A	N/A	None	N/A
What special tools are required to service this truck?	None	None	None	None	None	None
Have any difficulties been encountered using the various tools required for this truck?	Yes; close working area	°N	oN o	No O	No	°Z
15. Physical Characteristics						
Length w/Forks (in.) w/c Forks (in.)	148 106	148 106	157 107	152.8 110.8	Std	160.3
Width (in.)	47.5 to 59	47.5	53.5	54.3	54	54.3
Overhead Guard Ht (in.)	88	88 Std	83	83	86.5	83
Collapsed Mast Ht (in.)	Mast Ht varies	89 Std	84	Unk	Unk	Unk
Max Fork Ht (in.)	182	130	120	Unk	Unk	Unk
Free Lift (in.)	Depends on area of use	19	0	Unk	Unk	Unk
Backrest Ht (in.)	48 Std	48 Std	None	Unk	Std	Unk
Tilt Forward (degrees)	6 Std	6 Std	Std	Std	Std	Unk
Rearward (degrees)	12 Std	12 Std	Std	Std	Std	Unk
Sideshift (in.) Left Right	N/A	N/A	N/A	Unk	Cnk Cnk	Unk
Carriage width (in.)	45 Std	45 Std	48	48	48	48

Fork Dimensions (in.) Length Width Trichose	30-48 5 Std	4248 5 1 75	48 5 1.7/8	k Cor Cor	8 9 8 9 8	Unk Unk Unk
Do the forks comply with ANSI MH 114 (Hook-Tyne Mount)	Yes	Yes	Yes	Unk	Yes	Unk
.(
Fork Adjustment Dimensions: Minimum (in.) Maximum (in.)	11.2 Std 42	10	18 48	Unk Unk	Unk Unk	Unk Unk
Seat Clearance to Underside of Overhead Guard (in.)	40 Std	40 Std	38	40.2 Std	39	40.2 Std
Wheel Base (in.)	66 Std	66 Std	65	65 Std	Std	75 Std
Drive Tire Tread Width (C to C) (in.)	45	45	45	44.4	4	44.4
Steer Tire Tread Width (C to C) (in.)	34.62	34.62	43.5	42.5	42	42.5
Drive Tire Size	8.15 x 15(s) 7.00 x 15(d)	8.15 x 15	8.25 x 15 x 12	Unk	8.25 x 15	Unk
Number	2&4	2	2	2	2	2
Steer Tire Size	6.50 x 10	6.50 x 10	7.00 x 12 x 12	Unk	7.50 x 10	Unk
16. Reliability, Availability, and Maintainability Characteristics	ty Characteristics					
General Data:						
Normal workday in clock-hours	15-18	24	∞ 0	8	80	80
Number of shifts per day	1 or 2	3	-	1-3	1	3
Total number of malfunctions requiring corrective maintenance	Unk	Unk	Unk	Unk	Unk	Unk
Total clock-hours expended to perform corrective maintenance	9	Unk	Unk	Unk	Unk	Unk
Total man-hours expended to perform corrective maintenance	9	Unk	Unk	Unk	Unk	Unk
Organizational	ЧΠ	ЧΠ	АШ	All	All	ЧΠ
Dealer	None	Warranty only	Engine/trans rebuilt	None	Trans rebuild	Engine/trans rebuild
Average downtime awaiting parts not in stock at dealer location	Less than 8 hr	None	No more than 24 hr	1 day to 3 weeks	Less than 48 hr	No more than 24 hr
Any particular systems or component failures (trend) contribute more to non-availability	None	Tie-rod ends which have been corrected	Differential transmission components	None	Major engine parts	Differential transmission components

°Z		Checks fluid levels	All except engine rebuild	No V	°Z	Seal leak allows engine oil to mix with hydraulic oil		No	No	oN O	ON.	Yes	Yes	Yes
Š		None	All maint	N _O	°Z	Location of battery		No	No	N _o	°Z	Yes	Yes	Yes
Š		None	All maint	No	Parts avail- ability not good	°Z	ide by:	No	No	Changed loca- tion of oil filter	°Z	Yes	Yes	Yes
Š.		Checks fluid levels	All except engine rebuild	°Z	°Z	Seal leak allows engine oil to mix with hydraulic oil	provement nature ma	No	No	N _o	°N	Yes	Yes	Yes
N _O		None	All maint	No V	° N	No	of a corrective or imp	Yes	Yes	Yes; welded muffler bracket	Yes; new ignition; moved air pick-up opening	Yes	Yes	Yes
No	the:	Checks fluid levels	Minor or major	No	N _O	°Z	any modifications	No	No	oN o	°Z	Yes	Yes	Yes
Is non-availability contributed to by design deficiency or the need for a modification?	What type of maintenance is performed by the:	Operator	Mechanics	Are any components replaced on a scheduled basis? If so, what components and what intervals?	Are you dissatisfied with any features of the equipment or your relationship with the manufacturer or dealer? (Specify)	Are there any undesirable or unsatisfactory operating characteristics associated with the equipment? (Specify)	Since purchasing the truck have there been any modifications of a corrective or improvement nature made by:	Manufacturer	Dealer	In-House	Is the user aware of any significant design changes to this model truck in the last year?	Are items requiring periodic main- tenance accessible?	Can components be replaced and adjusted with minimum drainage and/or disturbance to other components?	Can periodic maintenance be performed with general-purpose tools normally associated with this type of equipment?

a those one necklome seculting from	No	No	N.	N	N.	MA
e mere any propents resummig from	INO	ON	NO	ON	No	ON
wtrama weather conditions each as						
Attende weather conditions such as						
old strating diffiguition antennas of						
old statility difficulties, elitibilities of						

No No No	if the following maintenance operations:	Weekly 3 wk 200 hr Weekly 30 min 30 min Unk 20 min	As needed No Sched 1200 hr As needed 5 min Unk 5 min	As needed No sched As needed 10 min Unk 10 min	Annually No sched 1200 hr Annually 10 min Unk 10 min	6 mo No sched 1200 hr 6 mo 30 min Unk 30 min		Weekly 3 wk 200 hr Weekly 10 min 10 min	Annually No sched 1200 hr Annually 30 min 10 min	No sched No sched 1200 hr No sched Unk Unk	No sched No sched 2400 hr No sched Unk Unk Unk	Weekly 3 wk 200 hr Weekly 10 min 30 min Unk 10 min		5-10 min None 5 min 5-10 min	30-40 min None None 30-40 min	N/A 2 hr 2 hr N/A
%	d for one man to perform each of the follo	4 wk Weekly We 10 min 5 min 30	4 wk Monthly As 10 min 10 min 5 r	As needed Monthly As 10 min 15 min 10	6 mo Monthly An 20 min 5 min 10	6 mo Monthly 6 r 20 min 5 min 30		4 wk Weekly We 20 min 15 min 10	6 mo Annually An 20 min 10 min 30	6 mo Yearly No 30 min 10 min Un	As needed As needed No 10 min 15 min Un	4 wk Weekly We 30 min 15 min 10		None None 5-1	None 1 hr 30	1 hr 35 min N/
Are there any problems resulting from extreme weather conditions such as cold starting difficulties, entrance of rain water into the operating components, etc.	Indicate the interval and average time required for one man to perform each of the following maintenance operations:		Air 4 v	Fuel As	Transmission 6 n Time 20	Hydraulic 6 n Time 20	Drain and Refill:	Engine Oil 4 w	Transmission Oil 6 n Time 20	Hydraulic Oil 6 n Time 30	Cooling System As Time 10	Lubrication 4 w	Preventative Maintenance Time:	Man-hours expended for daily No servicing (Av)	Man-hours expended for weekly No preventative maintenance servicing (Av)	Man-hours expended for monthly 1 h

18. Component Replacement Data

	15
nd replace:	0
e man to remove and replac	3
or on	30
e (min) required f	
average time (
Indicate the	Alternator

Alternator	30	30	15	45	Unk	15
Starter	45	45	20	45	Unk	20
Voltage Regulator	30	30	10	10	Unk	10
Battery	2	S	10	10	Unk	10
Fan Belt	30	30	20	10	Unk	20
Hydraulic Pump	06	06	06	120	Unk	8
Brake Shoes	09	09	120	240	Unk	120
19. Safety and Human Factors (User Comments)	ents)					
Do you augment the manufacturer's safety precautions?	Š	No O	Yes	No	No	Yes
Do you know of any safety hazards that exist during:	exist during:					
Operation Maintenance	22	° ° °	Visibility No	% % %	% % %	Visibility No
Are the following safety and human-factors items/elements furnished as standard or optional equipment adequate?	rs items/elements fu	rnished as standard or	optional equipment	adequate?		
Gauges and monitors	Yes	Yes	Yes	Yes	Yes	Yes
Controls within easy reach and clearly marked?	Yes	Yes	Yes	Yes	Yes	Yes
Anti-skid walkway surface	Yes	Yes	Yes	Yes	Yes	Yes
Does operator's size inhibit his performance?	°N	S.	Š	No O	No	% %
Do any safety hazards exist?	No	No	No O	°Z	No	No
Does the sound level cause operator fatigue after prolonged operation?	No O	No	No.	No	No	% S
Is special training required for:						
Operators	No	Yes	No oN	No.	No No	No
Maintenance Personnel	Yes. Hydro- static Trans- mission School	°N	No O	Ŷ.	% 9	å

20. Manuscrip.'s, Manuals, Tools, and Test Equipment (User Comments)

Were operator, maintenance, and parts manuals furnished with the item of equipment	No; requested for each truck	Yes	Yes	Yes	Yes	Yes
Are technical bulletins provided periodically by:	by:					
Dealer? Manufacturer?	No No	Yes Yes	Yes	% % %	Yes	Yes
Do you use the commercial manual as supplied by the manufacturer/dealer?	Yes	Yes	Yes	Yes	Yes	Yes
Have any difficulties been encountered using the manuals as reference in the following areas:	g the manuals as re	ference in the follow	ing areas:			
Operating/setup instructions?	No	No	No	No	No	S.
Servicing instruction?	No	No	No	No	No	Š
Adjustments?	No	No	No	No	No	Š
Repair and maintenance?	No	No	No	No	No	No.
Are special tools required by operators or mechanics to maintain or test/troubleshoot any portions of the equipment?	°Z	°Z	No	SO.	S S	8
Are special tools provided by the manufacturer?	N/A	N/A	N/A	N/A	N/A	Z
Are special tools described in the manual?	Yes	N/A	N/A	N/A	N/A	Z
Is the use of special tools sufficiently described in the operator/repair manual?	Yes	N/A	N/A	N/A	N/A	Z
21. Training and Logistic Support						
Are dealer repairs performed promptly?	Yes	Yes	Yes	No	Yes	Yes
Any difficulty in training operator and/or maintenance personnel?	No	No	No	No No	No	S.
Is timely technical assistance available when required:	required:					
From Dealer?	Yes	Yes	Yes	No	Yes	Yes
From Manufacturer?	Yes	Yes	Yes	Yes	Yes	Yes
Would you purchase like additional and/or replacement items?	Yes	Yes	Yes	Yes	Yes	Yes
Do you attempt to standardize names and/or models of equipment/ components within your fleet?	Yes	Yes	Yes	Yes	Yes	Yes

What is the length of warranty in equipment hours/months?	6 mo or 1000 hr	6 mo or 1000 hr	1 yr	90 days	1 yr	1 yr
What is the total number of warranty claims?	Very few	2 for 10 trucks	Unk	Unk	None	Unk
Are delays frequently caused by the lack of timely receipt of repair parts?	No	No	No	Unk	No	o N
What repair parts do you keep on hand for this item? If none stocked, why not?	Almost every- thing	None; parts readily available	Most parts	Most parts	None	Most parts
What is the length of time to fill emergency orders when parts are not in dealers stock?	8-16 hr	4-8 hr	2-3 days	1-21 days	24 hr	2-3 days
What is the length of time to fill normal orders when parts are not in dealers stock?	1 wk	8-24 hr	2-3 days	1-21 days	48 hr	2-3 days

DISTRIBUTION FOR MERADCOM REPORT 2230

No. Copies	Addressee	No. Copies	Addressee
	Department of Defense	1	Commander TARCOM
1	Commander Defense Construction and Supply Center		DRSTA-WS Warren, MI 48090
	DCSC-SS Columbus, OH 43215	2	Commander TARCOM
12	Defense Documentation Center Cameron Station		DRSTA-MVM Warren, MI 48090
	Alexandria, VA 22314	2	Commander TARCOM
1	Department of the Army Commander		DRSTA-QKC Warren, MI 48090
1	US Army Materiel Development and Readiness Command ATTN: DRCDE-DS 5001 Eisenhower Avenue Alexandria, VA 22333	1	Commander US Army Logistics Evaluation Agency DALO-LEI New Cumberland Army Depot
1	Commander US Army Maintenance Management Center		New Cumberland, PA 17070
	ATTN: DRXMD-EV Lexington Bluegrass Army Depot Lexington, KY 40507	1	Commander, HQ TRADOC ATTN: ATEN-ME Fort Monroe, VA 23651
1	Commandant US Army Quartermaster School ATTN: ATSM-CD-M Fort Lee, VA 23801	1	Commander Packaging, Storage and Containerization Ctr DRXTO-T Tobylonna Army Denot
1	Commander US Army Logistics Center		Tobyhanna Army Depot Tobyhanna, PA 18966
	ATTN: ATCL-ET Fort Lee, VA 23801	2	Commander US Army Materiel Development and Readiness Command
1	Commander US Army Test & Evaluation Com ATTN: DRSTE-AR Aberdeen Proving Grown, MD		Ammunition Ctr SARAC-DEV Savanna, IL 61704
1	21005 Commandant	1	Chief, Engineer Division DCSLOG ATTN: AFKC-LG-E
	US Army Transportation School ATTN: ATSP-CTD-MC Fort Eustis, VA 23604		HQ Sixth US Army Presidio of San Francisco, CA 94129
1	Commander TARCOM DRSTA-GBC Warren, MI 48090	1	Commander US Army Aberdeen Proving Ground ATTN: STEAP-MT-U (GE Branch) Aberdeen Proving Ground, MD 21005

No. Copies	Addressee	No. Copies	Addressee
1	Commander US Army Troop Support & Aviation Materiel Readiness Command ATTN: DRSTS-KTE 4300 Goodfellow Blvd St Louis, MO 63120		Chief, Cam & Topo Lab, DRDME-R Chief, Mar & Br Lab, DRDME-M Chief, Ctr Intrus Lab, DRDME-X Chief, Matl Tech Lab, DRDME-V Director, Product A&T Directorate, DRDME-T CIRCULATE
1	HQ, USAREUR & Seventh Army DCSENGR, ATTN: AEAEN-MO ATTN: Mil Ops Div APO New York 09403	1 5 50	Mech & Constr Eq Lab, DRDME-H Mech Eq Engr Div, DRDME-HM Warehouse & Depot Grp, DRDME-HM
1	Commander USA DARCOM Installation and Services Activity	1 3 3	Project Officer for Commercial Equipment, DRDME-HC Tech Reports Ofc, DRDME-WP Security Ofc (for liaison officers),
	ATTN: DRCIS-RI Rock Island, IL 61201	2	DRDME-S Tech Library, DRDME-WC Plans, Programs & Ops Ofc,
1	President US Army Armor and Engineer Board ATTN: ATZK-AE-TD-E Fort Knox, KY 40121	1	DRDME-U Pub Affairs Ofc, DRDME-I Ofc of Chief Counsel, DRDME-L
1	Commander OTEA CSTE-POD 5400 Columbia Pike Falls Church, VA 22091	1	Commanding Officer Navy Ships Parts Control Ctr (Code 3456) Mechanicsburg, PA 17055
2	GSAFSS Rm 1009 CM4 ATTN: Mr. Smith, Mr. McQuire Washington, DC 20406	1	Commandant of the Marine Corps HQ Marine Corp (Code LME-Mr. Zapf) Washington, DC 20380
1	Commander HQ DLA ATTN: DLA-OW Cameron Station, VA Alexandria, VA 22314 MERADCOM	1	Department of the Air Force AFLC CASO/LODS Federal Center Battle Creek, MI 49016
1	Commander, DRDME-Z Technical Director, DRDME-ZT Assoc Tech Dir/R&D, DRDME-ZN Assoc Tech Dir/Engrg & Acq, DRDME-ZE Spec Asst/Matl Asmt, DRDME-ZG Spec Asst/Tech Asmt, DRDME-ZK CIRCULATE		
1	Chief, Ctrmine Lab, DRDME-N Chief, Engy & Wtr Res Lab, DRDME-G Chief, Elec Pwr Lab, DRDME-E		